

PERFORMANCE TRUCK - HOUSTON

6855 North Loop 610 East, Houston, Texas 77028

Phone: (713) 844-7111

BUYER'S ORDER

Date Prepared: 11-06-2018	Delivery Date: 02-25-2019	Salesman: Preston Fredrich	Branch: Houston
Purchaser: Fort Bend County Road & Bridge		Telephone: 281-342-4513 Fax: 281-238-3635	
Mailing Address: P.O. Box 148 City: Richmond State: TX Zip: 77406			County: Fort Bend
Physical Address: 201 Payne Lane City: Crabb State: TX Zip: 77469			County: Fort Bend
Description: NEW 2020 KENWORTH T880			
Mileage:	Color: BLUE Baffin Blue	NOTE: BUYBOARD CONTRACT# 521-16	
VIN: TO ORDER Comments: See attached vehicle summary, quote ID # C0816518.			
Purchaser's Agent: Les Miller		Title: General Manager Fleet Operations	License Type: Apportioned Account # Fort Bend County

LICENSE - TITLE INFORMATION

Months: 12	Tractor:	Truck: X	Trailer:	Body Type: OTHER	Color: BLU	Tons:	GCW: 66000
Apportioned: X	IMC #	Combination:	Com'l:	Token Trailer:	Gas:	Diesel: X	

INSURANCE INFORMATION

AGENCY:	SELLING PRICE	264,662.00
NAME:	ACCESSORIES	-
PHONE:	CASH PRICE W/ACCESS.	264,662.00
LIEN INFORMATION		
NAME:	TRADE IN ALLOWANCE	-
LIEN DATE:	NET CASH DIFFERENCE	264,662.00
ADDRESS:	FEDERAL RETAIL EXCISE TAX	-
PHONE:	NET PRICE	264,662.00
CITY, STATE, ZIP:	STATE SALES TAX	-
COMMENTS:	LICENSE MO. & FEE	-
AMOUNT:	TITLE FEE (INCLUDES \$5 TAG FEE)	5.00
NAME:	COMMERCIAL INSPECTION FEE	-

ADDITIONAL INFORMATION

BUYBOARD CONTRACT # 521-16	DEALER'S INVENTORY TAX	-
Proposal is for one Kenworth T880 Truck	DOCUMENTARY FEE*	75.00
See Attached Specs	EXTENDED WARRANTY	4,530.00
Pricing is per Unit	SUBTOTAL	269,272.00
Payment in full at time of Delivery	BALANCE OWED ON TRADE	-
Extended Warranty Includes 5 Year / 100,000 Engine, AfterTreatment, Base Vehicle	SUBTOTAL	269,272.00
Includes Installation of BIG JOHN 100D Tree Spade	PREPAYMENT	-
Deliver From Arkansas to Fort Bend County	BALANCE DUE UPON DELIVERY	269,272.00

DISCLAIMER OF WARRANTY

Any warranties on the products sold hereby are those made by the manufacturer. The seller, CLEVELAND MACK SALES, INC., PERFORMANCE TRUCK OR PERFORMANCE TRAILER, hereby expressly disclaims all warranties, either express or implied, including any implied warranty of merchantability or fitness for a particular purpose, and CLEVELAND MACK SALES, INC., PERFORMANCE TRUCK OR PERFORMANCE TRAILER neither assumes nor authorizes any other person to assume for it any liability in connection with the sale of said products.

* A DOCUMENTARY FEE IS NOT AN OFFICIAL FEE. A DOCUMENTARY FEE IS NOT REQUIRED BY LAW, BUT MAY BE CHARGED TO BUYERS FOR HANDLING DOCUMENTS RELATING TO THE SALE. A DOCUMENTARY FEE MAY NOT EXCEED A REASONABLE AMOUNT AGREED TO BY THE PARTIES. THIS NOTICE IS REQUIRED BY LAW.

Vehicle(s) are subject to prior sale and will not be held more than five working days.

PURCHASER _____

THIS ORDER NOT BINDING UNTIL ACCEPTED BY DEALER.

SALESPERSON _____

ACCEPTED BY _____



Performance Truck C359
6855 North Loop East

Houston, Texas United States 77028

Phone: (361) 798-0902

Fax:

Email: pfredrich@performancetruck.com

Phone:

Fax:

Contact Email:

Prepared for:

Vehicle Summary

Unit		Chassis	
Model:	T880 Series Conventional	Fr Axle Load (lbs):	20000
Type:	FULL TRUCK	Rr Axle Load (lbs)	46000
Description:	364647	G.C.W. (lbs):	80000
Application		Road Conditions:	
Intended Serv.:	Local pickup & delivery.	Class A (Highway)	89
Commodity:	Vehicles which haul	Class B (Hwy/Mtn)	10
	Other dry goods	Class C (Off-Hwy)	01
		Class D (Off-Road)	00
		Maximum Grade:	6
Body		Wheelbase (in):	264
Type:	End dump	Overhang (in):	100
Length (ft):	20.0	Fr Axle to BOC (in):	74
Height (ft):	13.5	Cab to Axle (in):	190
Max Laden Weight (lbs):	6000	Cab to EOF (in):	290
Trailer		Overall Comb. Length (in):	412
No. of Trailer Axles:	0	Special Req. U.S. Domestic Registry, 50-State	
Type:			
Length (ft):	0.0		
Height (ft):	0.0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	120		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/6/2018 4:12:01 PM

Effective Date: Jan 1, 2018

Prepared by: Preston Fredrich

Complete

Model Number: T880 Series Conventional

Quote/DTPO/CO: C0816518

Version Number: 41.00



Performance Truck C359
6855 North Loop East

Houston, Texas United States 77028

Phone: (361) 798-0902

Fax:

Email: pfredrich@performancetruck.com

Phone:

Fax:

Contact Email:

Prepared for:

Description		Weight
Model		
	T880 Series Conventional	15,073
	T880	0
	Chassis operation will not include a stationary application. Stationary operation is defined as running the engine under load while stationary at a substantial fraction of engine gross horsepower (60% or greater) for an extended period of time (longer than 5 - 10 minutes).	0
	CARB Idle Emissions Reduction - Cummins	0
	Non-Sleeper w/rear axle capacity less than 59K.	0
	Other dry goods	0
	Local pickup & delivery. Vehicles which haul freight, typically operating within a 100-mile radius, on public streets & highways, & other paved surfaces, including limited Class C roads. Includes package & freight delivery, as well as fuel oil or petroleum distribution, etc. Road usage: minimum 3% Class B, do not code for Class D.	0
	End dump	0
	U.S. Domestic Registry, 50-State	0

Engine & Equipment

X15 450 2017 450@1800 1650@1000	300
w/Intebrake, Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. Linehaul, Efficiency Series	
N09200 N205 65...Standard Maximum Speed Limit [LSL]	
N09220 N207 0....Expiration Distance	
N09240 P13 120...Hard Maximum Speed Limit	
N09260 P14 64...Maximum Accelerator Pedal Vehicle Speed	
N09300 P19 64...Maximum Cruise Speed	
N09360 N203 252...Reserve Speed Function Reset Distance	
N09380 N202 0....Maximum Cycle Distance	
N09400 N206 10...Maximum Active Distance	
N09420 N201 0....Reserve Speed Limit Offset	
N09440 P11 NO...Engine Protection Shutdown	
N09460 P06 NO...Gear Down Protection	
N09480 P26 1400.Max PTO Speed	
N09500 P02 NO...Cruise Control Auto Resume	
N09520 P04 NO...Auto Engine Brake in Cruise	
N09540 N209 0....Expiration Distance	

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/6/2018 4:12:01 PM

Effective Date: Jan 1, 2018

Prepared by: Preston Fredrich

Complete

Model Number: T880 Series Conventional

Quote/DTPO/CO: C0816518

Version Number: 41.00

Description		Weight
N09560 P520	YES..Enable Idle Shutdown Park Brake Set	
N09580 P32	5....Timer Setting	
N09600 P233	YES..Enable Impending Shutdown Warning	
N09620 P234	60....Timer For Impending Shutdown Warning	
N09640 P516	35....Engine Load Threshold	
N09680 P33	NO...Idle Shutdown Manual Override	
N09720 P230	YES..Enable Hot Ambient Automatic Override	
N09740 P46	40....Low Ambient Temperature Threshold	
N09760 P56	60....Intermediate Ambient Temperature Threshold	
N09780 P47	80....High Ambient Temperature Threshold	
Prospector Version 43.0		0
Replaces 42.1		
Effective VSL Setting NA		0
Engine Idle Shutdown Timer Enabled		0
Enable EIST Ambient Temp Override		0
Enable EIST in PTO Mode		0
Use only with MX and Cummins engines		
Eff EIST NA Expiration Miles		0
Use only with MX and Cummins engines		
Air compressor: Cummins 18.7 CFM, Naturally		0
Aspirated for Cummins X15 engines		
Air Cleaner: composite firewall mounted PACCAR or		0
Cummins engines		
Pre-cleaner mounted in the hood plenum		0
Fan Hub: Horton 2-Speed for X15		0
Cooling module: 1330 square inches.		0
Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant.		
Radiator bug screen mounted between hood &		2
grille.		
Exhaust: 2017 EPA RH Under DPF/SCR w/ RH		0
side of cab vertical tailpipe w/ daycabs, extended daycabs, or modular sleepers.		
Tailpipe: 5 in. single 24 in. 45 degree curved.		-3
Fuel Filter:PACCAR Standard Service Interval		0
Fuel/Water Separator. 2017 Emissions		
Run Aid:None		0
*For Fuel Filter		
Start Aid:None		0
*For Fuel Filter		

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/6/2018 4:12:01 PM	Complete	Model Number:	T880 Series Conventional
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	C0816518
Prepared by:	Preston Fredrich		Version Number:	41.00



Description	Weight
Kenworth Fuel Cooler Required for Cummins engines with a single fuel tank. Required for PACCAR MX-13 engine with a single fuel tank and stationary use: High RPM, low vehicle speed, sustained for longer than 1 hour. Optional for all other applications.	6
Alternator: PACCAR 160 amp, brush type	0
Batteries: 3 PACCAR GP31 threaded post (700-730) 2100-2190 CCA dual purpose.	0
Starter: PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
12V low voltage disconnect for starter battery protection.	0
Remote PTO/Throttle, 12-Pin, Engine Bay Remote Control Provision	0
Decline Driver Performance Assistant (DPA)	0
Transmission & Clutch	
Eaton AMT LSM Package - Vocational Config Low Speed Maneuverability, Rev=Blended Pedal, Drive=Urge to Move, Manual=Standard, Low=Blended Pedal Eaton AMT Low Speed Maneuverability parameters to utilize various Eaton low speed functions depending on transmission shift selection (Reverse, Drive, Manual, Low). Eaton service tool can be utilized to reconfigure parameters individually if customer desires something other than typical Linehaul or Vocational package options.	0
Fuller Advantage Automated FAO-16810C-EA3 10Speed No Cooler w/ HSA *Use w/ 2250385 Only.	221
Clutch: UltraShift Plus Or Fuller Advantage Series Automated transmissions.	0
Driveline: 2 Meritor RPL25 SD; 1 Centerbearing Require 3500064 *Replaces code 2408501.	77
First Transmission PTO compatibility - Chelsea 230/236/238/442/489/660/680-V3 or Muncie CS8/SH8/TG8S-P1 bottom mounted 6 or 8-Bolt PTO's for all Eaton & PACCAR transmissions. This application includes use of the standard hydraulic clutch actuator on Eaton FR & RT transmissions and supports bottom mounted 6 and 8-Bolt PTO's with single acting air actuation.	0
Rear transmission support springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	0
First Customer Installed Eaton/PACAR Trans PTO.	0
Aluminum clutch housing	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/6/2018 4:12:01 PM
Effective Date: Jan 1, 2018
Prepared by: Preston Fredrich

Complete

Model Number: T880 Series Conventional
Quote/DTPO/CO: C0816518
Version Number: 41.00

	Description	Weight
Front Axle & Equipment		
	PACCAR Front Axle rated at 20K, standard track, 4 in. drop.	156
	Front Brakes: 14,601-22K Bendix air disc brakes.	10
	Splined rotor for front air disc brakes for use with aluminum hubs.	0
	Front Hubs Aluminum hub pilot 20,000 lbs. 16.5x6in. or 7in. or air disc brakes. 10 Bolt, 11-1/4 in. bolt circle.	16
	ConMet PreSet Plus Hub package; front axle.	0
	Hubcap: front vented.	0
	Slack Adjusters included w/ front axle or brake. Also use w/ disc brakes.	0
	Front Springs: Taperleaf 20K w/ shock absorbers w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins except for C500 which has threaded pins. Not available on W900L. W900B use 2866021.	241
	Dual power steering gear: 16-22K Sheppard HD94. Heavy duty. Not for use on T3.	73
	Power Steering Cooler:Radiator Mounted Air-to-Oil	11
	Threaded Bushings for taperleaf spring 16K, 18/20K, 22K, 40K replacing rubber.	0
Rear Axle & Equipment		
	Dual Meritor RT46-160 rear axle rated at 46K. Tandem rear axles.	534
	Rear Axle Ratio - 3.91.	0
	Dual Rear Brakes 16-1/2x7 in. to 46K; Bendix ES-extended service S-cam.	0
	Dual Rear Brake Drums: cast.	0
	Dual Rear Hubs: Aluminum hub pilot 46K 11-1/4 in. bolt circle.	0
	ConMet PreSet Plus Hub package; dual rear axle.	0
	Dual Rear axle automatic slack adjusters.	0
	Spring Brake: 3030 long stroke dual 30 square inches travel; replaces standard 2-1/2 in. travel. Helps keep brakes in adjustment longer.	4
	Bendix 4S/4M anti-lock brake system w/ air traction control (ATC).	2
	Driveline: 1 Meritor RPL20 Interaxle; Replacing I/A *Use W/ RPL 25 Main D/L	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/6/2018 4:12:01 PM	Complete	Model Number:	T880 Series Conventional
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	C0816518
Prepared by:	Preston Fredrich		Version Number:	41.00

Description	Weight
Driver Controlled Differential Lock (Crosslock) for Meritor Axles 40K to 52K forward rear & rear rear axle. Under Speed Interlock is standard on T680.	39
Separate switch for dual axles: differential lock or crosslock.	0
Rear suspension: Tandem Hendrickson RT463 46K. 54 in. axle spacing. Steel beams & barpin bushing. 6 in. saddle height. Unladen Height: 11.1 in. Laden Height: 10 in.	573
Heavy-duty gussets for forward suspension crossmember on Airslide 400/460, Chalmers, or Hendrickson beam suspensions. This replaces the standard gussets.	12

Tires & Wheels

Front Tires: Goodyear Endurance WHA 315/80R22.5 20PR.	62
Rear Tires: Yokohama MY507 11R22.5 16PR	120
Rear Tire Quantity: 8	0
Front Wheel: Accuride 29039 22.5X9 steel Steel Armor[TM] powder coat, hub-pilot mount. 10000lb. maximum rating. 5-hand holes.	70
Rear Wheel: Accuride 51487 22.5x8.25 steel Steel Armor[TM] powder coat, hub-pilot mount. 7400lb. maximum rating. 5-hand hole. Air disc brake compatible. Code is priced per pair of wheels.	0
Powder coat white steel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
Rear Wheel/Rim Quantity: 8	0

Frame & Equipment

Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 337 in. to 416 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80, RBM is 1,776,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	416
Full Steel Insert: for 10-5/8 in. or 10-3/4 in. Steel 337 in. to 416 in. or 2nd insert for 11-5/8 in. steel frame. Adds 1,149,000 in.-lb to main rail RBM. Truck insert weight is 2.05 lb.-in. per pair of rails. Full frame insert length is equal to wheelbase plus rear frame cutoff plus dimension forward of front axle by model: T660, T680, T800, T880 = 21.26 in.; C500B = bumper setting minus 0.79 in.; W900B = 5.27 in., W900L = 1.50 in., W900S = 3.27 in.; T440/T470 50 in. bumper setting = 21.26 in., T470 73 in. bumper setting = 72.3 in.	789
Bumper: Tapered polished aluminum channel. Requires a bumper setting code.	-6
48.5 in. Bumper setting. Requires a bumper code.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/6/2018 4:12:01 PM	Complete	Model Number:	T880 Series Conventional
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	C0816518
Prepared by:	Preston Fredrich		Version Number:	41.00

Description	Weight
Front tow hook: Center mounted, cast. Requires iron front drive brackets.	28
Brackets: Iron front spring drive. Included with front spring capacity of 16,000 lbs or greater; code not required.	47
Battery box cantilever steel BOC w/ fiberglass cover.	24
Battery box location: RH Side.	15
T470,C5, T6, T8 non-polished DPF/SCR or CNG cover diamond plate w/ step. For use w/ 2010 or later exhaust systems. For T8, use extended length non-polished battery box on opposite rail to match the length of under cab components. End plates will be painted standard black frame color.	0
2017 EPA Emissions Engine	0
Rear mudflap arms: Betts B-25 standard-duty, straight. Includes B1732 mounting brackets as standard.	0
Rear mudflap shields: White plastic antisail w/ Kenworth logo.	0
Square end-of-frame w/o crossmember; non-towing.	0
Fuel Tanks & Equip	
Fuel Tank: 90 US gallon 24.5in. aluminum under replace. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck.	-4
DEF tank 7.3 clear BOC [CBOC], requires LH under cab fuel tank. This tank has 7.3 gallons of usable volume. The tank will be located inboard of the LH under cab fuel tank. There is no frame space required to locate this tank. Not for use on sleeper chassis. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	-23
Standard DEF to fuel fill ratio: 2:1 or greater.	0
Anti-siphon device swaged in place. For any number of fuel tanks.	0
DEF tank location is on the LH.	0
Location: 90 gal fuel tank LH under cab	0
Cab & Equipment	
Cab: Stamped aluminum cab with panoramic curved glass windshield. Standard with stamped aluminum doors, heavy duty in-swinging hinges, and triple sealed doors. Manufactured using self-piercing rivets and structural adhesive. Includes LED exterior marker lights and turn signals.	0
Hood: T880 Standard Length With Mechanically Fastened Fenders. 122.6 inch BBC.	15

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/6/2018 4:12:01 PM	Complete	Model Number:	T880 Series Conventional
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	C0816518
Prepared by:	Preston Fredrich		Version Number:	41.00

Description	Weight
Fine particulate filter for cabin air HVAC system. To provide extra filtration in high dust applications. Cabin airflow is reduced with this additional filter. *Cannot be used with code 8108003.	0
Cab HVAC - Day Cab and 40in Sleeper System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper.	0
Kenworth Smartwheel: 18 in. Non-Leather With Integrated Radio and Cruise Controls.	0
Column Mtd TMSN Control W/Retarder Cntrl, RH Side Use with Automated and Automated Manual Transmissions Only	0
Adjustable telescoping tilt steering column.	0
5 sets of keys. Replaces standard 2 sets of keys.	0
Key Lock: Customer Specified Tumbler Part Number Includes ignition, cab doors and if applicable, sleeper tool box door. G key will not work on new P lock and ignition	0
Dash Mounted Compact Trailer Brake Valve. Self Returning.	0
Dash Switch: 1st Single-Acting Eaton or PACCAR Mounted PTO. Electric switch, wiring, software, air solenoids, and plumbing are factory-installed to control the 1st Eaton (single-acting) trans PTO.	0
One spare switch: Wired to power.	0
Custom key code: 7-pin (P0986)	0
Gauge: Dash mounted air filter restriction gauge.	0
Gauge: Engine Oil Temperature Gauge With Integral warning light. The NavPlus HD unit includes a virtual engine oil temperature gauge.	0
Gauge: Fuel filter restriction gauge.	0
Gauge: Oil Temperature Gauge Transmission. The NavPlus HD unit includes a virtual transmission oil temperature gauge.	0
Kenworth Driver Performance Center:5in Full Color high resolution Thin Film Transistor (TFT) active matrix display with advanced driver information including fuel economy performance, outside air temp, clock, odometer and trip, engine hour meter, ignition timer, engine RPM, general truck information, diagnostics, and gear display. All Highline functionality is accessed via the Kenworth MCS providing intuitive control at the driver's fingertips. Also includes Dark Cabin functionality. When activated, the only interior light that will function when a door is opened is the door courtesy lamp.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/6/2018 4:12:01 PM	Complete	Model Number:	T880 Series Conventional
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	C0816518
Prepared by:	Preston Fredrich		Version Number:	41.00

Description	Weight
Kenworth instrumentation and control package with 9 standard easy-read gauges: includes speedometer, tachometer, fuel gauge, engine coolant temp, engine oil pressure, voltmeter, dual air pressure, air application pressure and DEF gauge. All accessory controls utilize electronically activated solenoids that include advanced vehicle protection interlocks.	0
Modular Dash Options: Dash storage unit with two shelves. Reduces total gauge count by 6.	0
Interior color: Slate Gray	0
Interior package: Vantage daycab Includes durable headliner and vinyl sidewalls with geometric patterned trim and anodized aluminum accents throughout. Convenient overhead storage cubbies, full size glove box, two center console cupholders, and large door pad map pocket. Standard LH/RH power windows, electric door locks, interior LED lighting, nighttime-friendly red ambient lighting for dash and footwell, and door mounted courtesy light. Includes two standard 12V power outlets. Driver sunvisor includes strap.	0
Rubber floormat	0
Driver Seat: GT701 HB with Vinyl material. The GT701 is standard with a single air bag, scissor linkage seat suspension. It includes a single chamber lumbar support, 10in Fore/Aft adjustment, 7in Up/Down adjustment, 2.5in pan extension, 51 degree seat back recline, and 16 degree full seat tilt. Includes 3-point matching seat belts. DR seat standard w/ dual armrests.	0
Rider Seat: GT100 Toolbox IB with Vinyl Material. The GT100 seats are standard with fixed base. Includes 3-point matching seat belts. Rider seat standard w/ LH armrest.	0
Seat color: Slate Gray with Gray stitching.	0
Driver and Rider Seat Belts: Orange Seat Belts. Replacing standard color.	0
Kenworth Radio with AM/FM/WB/USB and Bluetooth	4
Base Level Audio System - Daycab:High Performance Door Speakers.	2
Non-self cancelling turn signal: W/column-mounted headlight dimmer switch & intermittent wiper control.	0
LH and RH Trip Ledge Rain Deflectors	0
Kenworth TruckTech+ The Kenworth Remote Diagnostics system provides the Worlds Best reporting of engine and aftertreatment fault codes, as well as enhanced support for the truck owner through rapid communication of fault severity and recommended actions. This option is Standard on all Kenworths with an MX engine.	0
Long grabhandle RH side mounted to side-of-cab exhaust.	2

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/6/2018 4:12:01 PM	Complete	Model Number:	T880 Series Conventional
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	C0816518
Prepared by:	Preston Fredrich		Version Number:	41.00

	Description	Weight
	Grabhandle: LH, Exterior, Side of Cab - Ergonomic Grab Handle Mounted To The Left Hand Exterior Of The Cab For Entry and Exit.	3
	Dual Cab Interior Grabhandles: A Pillar Mounted Dash Wrap and B Pillar Mounted Grabhandles	0
	Kenworth Daylite Door with standard LH/RH electric door locks and LH/RH electric window controls.	0
	Single air horn under cab.	0
	Look-Down, Pass. Door, Black 11x6	0
	Aero Mirror: Dual Kenworth Aerodynamic Motorized heated mirrors, 7in X 13in with cab color mirror shell and black mirror arms. Also includes LH/RH heated 6in X 7in convex mirrors. Mirror brackets set for 8-1/2 ft load width. Mirror controls located on driver side door pad.	0
	Rear cab stationary window 19in x 36in	0
	One-piece bonded-in windshield with curved glass. Standard.	0
	Wheelwell Fender Extension: 2.5 Inches	4
	Kenworth Cab/Sleeper Air Suspension.	0
Lights & Instruments		
	Headlamps: SAE Dual Halogen Complex Reflector	0
	Marker Lights: Five, rectangular, LED	0
	Turn Signal Lights: Flush mounted LED mounted at top of fender wheel arc	0
	LED Stop,Turn,Tail: With Two LED Backup Lights and With An LED License Plate.	0
	Dual Flush Floodlights: First Set	2
	Floodlight Location: Located Low - First Set . This Code To Be Used With Flush-Mount (9052011) or C/I (9058071) Codes Only.	0
	Headlamps to turn on when wipers are active.	0
	Marker Lights: Interrupter Switch. Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash.	0
	Electric Backup Alarm: Meets SAE J994 & OSHA requirements.	4
	Polyswitches replacing fuses. Switch will automatically reset after removal of excess load.	0
Air Equipment		
	Air Dryer: Bendix AD-IS Extended Purge heated. with PuraGuard	4

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/6/2018 4:12:01 PM	Complete	Model Number:	T880 Series Conventional
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	C0816518
Prepared by:	Preston Fredrich		Version Number:	41.00

	Description	Weight
	Moisture ejection valve w/ pull cable drain.	0
	Full truck kit: Gladhands mounted at end-of-frame. Seven-way female receptacle mounted at end-of-frame in taillamp bracket. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve, tractor protection valve, and spring brake inversion/relay valves are standard.	15
	Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing.	0
	Trailer ABS electric supply through SAE J560 7-pin connector per TMC RP137).	0
Extended Warranty		
	Base Warranty - Standard Service Heavy Duty 12 months / 100,000 miles / 160,000 km.	0
Miscellaneous		
	Ship to Specific Address. N94010 Big John N94020 909 N94030 Heber Springs, AR 72543 N94040 DANNY MAN	0
	GHG Secondary Manufacturer: Does Not Apply	0
	Warning triangle reflector kit: Shipped loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	4
	One 5 lb. dry chemical type fire extinguisher mounted outboard of driver seat. Class ABC.	11
	Zinc Phosphate frame rail paint processing. Requires frame rail code. Code is for 1 pair of rails.	0
	CECU/VECU Electronics Architecture	0
Promotions		
	2019 2ND HALF FCA - HD	0
	SPECIAL INVOICING - CUMMINS LTA - X15	0
Paint		
	Paint color number(s). N97020 A - L0436 SIERRA BLUE N97200 FRAME N0001 BLACK	0
	Bumper Unpainted	0
	Day Cab Standard Paint	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/6/2018 4:12:01 PM
Effective Date: Jan 1, 2018
Prepared by: Preston Fredrich

Complete

Model Number: T880 Series Conventional
Quote/DTPO/CO: C0816518
Version Number: 41.00



Description	Weight
1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0
	0
Total Weight	18955 lb

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/6/2018 4:12:01 PM	Complete	Model Number:	T880 Series Conventional
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	C0816518
Prepared by:	Preston Fredrich		Version Number:	41.00