

**REVIEW BY FORT BEND COUNTY
COMMISSIONERS COURT**

**Fort Bend County
Engineering Department**
301 Jackson Suite 401
Richmond, Texas 77469
281.633.7500
Permits@fortbendcountytexas.gov

☒ Right of Way Permit
☐ Commercial Driveway Permit

Permit No: 2017-13964

Applicant: CivilCorp, LLC

Job Location Site: Trammel-Fresno Road, Missouri City, TX 77459

Bond No. Not Required **Date of Bond:** _____ **Amount:** _____

The above applicant came to make use of certain Fort Bend County property subject to, "The Order Regulating the Laying, Construction, Maintenance, and Repair of Buried Cables, Conduits, and Pole Lines, In, Under, Across or Along Roads, Streets, Highways, and Drainage Ditches in Fort Bend County, Texas, Under the Jurisdiction of the Commissioners Court of Fort Bend County, Texas," as passed by the Commissioners Court of Fort Bend County, Texas, of the Minutes of the Commissioners Court of Fort Bend County, Texas, to the extent that such order is not inconsistent with Chapter 181, Vernon's Texas Statutes and Codes Annotated.

Notes:

1. Evidence of review by the Commissioners Court must be kept on the job site and failure to do so constitutes grounds for job shutdown.
2. Written notices are required:
 - a. 48 hours in advance of construction start up, and
 - b. When construction is completed and ready for final inspection, submit notification to Permit Administrator thru MyGovernmentOnline.org portal.
3. This permit expires one (1) year from date of permit if construction has not commenced.

On this 18th day of July, 2017, Upon Motion of Commissioner Meyers, seconded by Commissioner Morales, duly put and carried, it is ORDERED, ADJUDGED AND DECREED that said notice of said above purpose is hereby acknowledged by the Commissioners Court of Fort Bend County, Texas, and that said notice be placed on record according to the regulation order thereof.

Signature


Presented to Commissioners Court and approved.

By: Charles O. Ay
for County Engineer

Date Recorded 7-21-2017 Comm. Court No. 9B

N/A
By: _____
Drainage District Engineer/Manager

Clerk of Commissioners Court
By: Aronda Williams
Deputy



**PERMIT APPLICATION REVIEW FORM FOR
CABLE, CONDUIT, AND POLE LINE ACTIVITY
IN FORT BEND COUNTY**

**Fort Bend County
Engineering Department**
301 Jackson Suite 401
Richmond, Texas 77469
281.633.7500
Permits@fortbendcountytexas.gov

- ☒ Right of Way Permit
☐ Commercial Driveway Permit

Permit No: 2017-13964

The following "Notice of Proposed Cable, Conduit, and/or Pole Line activity in Fort Bend County" and accompanying attachments have been reviewed and the notice conforms to appropriate regulations set by Commissioner's Court of Fort Bend County, Texas.

(1) COMPLETE APPLICATION FORM:

- ☒ a. Name of road, street, and/or drainage ditch affected.
☒ b. Vicinity map showing course of directions
☒ c. Plans and specifications

(2) BOND:

- ☐ County Attorney, approval when applicable.
- ☐ Perpetual bond currently posted. Bond No: _____ Amount: _____
- ☐ Performance bond submitted. Bond No: _____ Amount: _____
- ☐ Cashier's Check Check No: _____ Amount: _____

(3) DRAINAGE DISTRICT APPROVAL (WHEN APPLICABLE):

Drainage District Approval

Date

We have reviewed this project and agree it meets minimum requirements.

Charles O. Ay


Permit Administrator

7/10/17
Date

INDEX OF SHEETS
SEE SHEET 2 FOR INDEX OF SHEETS

STATE OF TEXAS TEXAS DEPARTMENT OF TRANSPORTATION PLANS OF PROPOSED STATE HIGHWAY IMPROVEMENT TRAMMEL FRESNO ROAD FORT BEND COUNTY CSJ 0912-34-143 PROJECT NO. C912-34-143

LIMITS: VICKSBURG BLVD TO FORT BEND PARKWAY
ROADWAY LENGTH: 3,394.05 FT = 0.643 MI
PROJECT LENGTH: 3,394.05 FT = 0.643 MI
FOR THE WORKING OF A NON-FREWAY ROADWAY
CONSISTING OF GRADING, STORM SEWERS, DRAINAGE
AND CONCRETE PAVEMENT



LOCATION MAP N.T.S.

EXCEPTIONS: NONE
RR CROSSINGS: NONE
EQUATIONS: NONE

© 2016 by Texas Department of Transportation
All rights reserved.

COUNTY FORT BEND PROJ. NO.
HWY. NO. TRAMMEL FRESNO LETTING DATE:
DATE ACCEPTED

MISSOURI CITY
TEXAS
DEPARTMENT OF PUBLIC WORKS
SCOTT R. ELMER, P.E., DIRECTOR


FIRM REGISTRATION NUMBER: 10283



Thomas C. Hylleberg
11/11/2016

CivilCorp
ENGINEERS & SURVEYORS
2825 ALICREST DR., SUITE 400, HOUSTON, TEXAS 77042
TEL: 2825-8100 FAX: 2825-8103 TOLL FREE: 877-234-2343

ALL BEARINGS AND COORDINATES SHOWN ARE BASED ON THE TEXAS STATE PLANE COORDINATE SYSTEM, SOUTH CENTRAL ZONE (4204) NAD 83 (2011), EPOCH 2010.01. ALL COORDINATES SHOWN ARE SURFACE ADJUSTMENT AND MAY BE CONVERTED TO GRID BY DIVIDING BY A 1X001 COMBINED ADJUSTMENT FACTOR OF 1.000130. ALL ELEVATIONS SHOWN ARE NAVD 88 GEOD109. ELEVATIONS WERE DETERMINED BY A RTX SURVEY (TXDOT VIRTUAL REFERENCE STATION NETWORK) AND HOLDING EXISTING CITY OF MISSOURI MONUMENTS (H-102, H-104, H-106, H-107) AS FIXED. H-103 & H-105 WERE ADJUSTED TO FOLLOW THE FOLLOWING TO MATCH THE OTHER MONUMENTS: ELEV. = -0.13. SPECIFICATIONS ADOPTED BY THE TEXAS DEPARTMENT OF TRANSPORTATION, NOVEMBER 1, 2014 AND SPECIFICATION ITEMS LISTED AND DATED AS FOLLOWS, SHALL GOVERN ON THIS PROJECT. REQUIRED SPECIAL LABOR PROVISIONS FOR STATE CONSTRUCTION PROJECTS: SP000--008.



VICINITY MAP N.T.S.

REGISTERED ACCESSIBILITY SPECIALIST (RAS)
INSPECTION REQUIRED TDLR NO. EABPRJ87806733

Texas Department of Transportation

CITY OF MISSOURI CITY
CONCURRENCE

11/11/16

APPROVED
FOR LETTING:

12/6/2016

Thomas C. Hylleberg
PROJECT MANAGER
Shawn M. Stalder
DISTRICT ENGINEER

DATE	BY	REVISION	NO.
09/12/14	143	CS	1

FUNCTIONAL CLASSIFICATION	2016 ADT	2036 ADT	DESIGN SPEED
URBAN MAJOR COLLECTOR	8,800	13,000	45

SHEET NO.

DESCRIPTION

GENERAL

- 1 TITLE SHEET
- 2 INDEX OF SHEETS
- 3 - 5 EXISTING TYPICAL SECTIONS
- 6 - 7 PROPOSED TYPICAL SECTIONS
- 8, 8A-8H GENERAL NOTES
- 9, 9A-9H ESTIMATE AND QUANTITY SHEET
- 10 SUMMARY OF REMOVAL QUANTITIES
- 11 SUMMARY OF ROADWAY QUANTITIES
- 12 - 13 SUMMARY OF DRAINAGE QUANTITIES
- 14 SUMMARY OF DETENTION POND QUANTITIES
- 15 SUMMARY OF PAVEMENT MARKING QUANTITIES
- 16 SUMMARY OF SMALL STONE
- 17 SUMMARY OF SMP3 QUANTITIES

TRAFFIC CONTROL PLAN

- 18 DETOUR LAYOUT

TRAFFIC CONTROL PLAN STANDARDS

- 19 - 30 BARRICADE AND CONSTRUCTION STANDARDS: BC(1)-14 THRU BC(12)-14
- 31 TRAFFIC CONTROL PLAN ONE-LANE TWO-WAY TRAFFIC CONTROL: TCP (1-2)-12
- 32 CONSTRUCTION SEQUENCE FOR MISCELLANEOUS DRIVES: CSMD TC 8010-09 (HOU)
- 33 TRAFFIC CONTROL PLAN TYPICAL DETAILS: WZ(TD)-13
- 34 WORK ZONE DEAD END ROADWAY DETAILS: WZ (HCD)-13

ROADWAY DETAILS

- 35 SURVEY CONTROL INDEX
- 36 HORIZONTAL & VERTICAL CONTROL
- 37 - 38 HORIZONTAL ALIGNMENT DATA
- 39 - 43 REMOVAL LAYOUT
- 44 - 52 ROADWAY PLAN & PROFILE

ROADWAY DETAILS STANDARDS

- 53 - 54 JOINTED REINFORCED CONCRETE PAVEMENT DETAILS: JRCP (HOU)
- 55 - 56 CONCRETE PAVEMENT JUNCTURES: CPJ (HOU)
- 57 CONCRETE CURB AND GUTTER: CGC-12
- 58 CONCRETE CURB AND DIRECTIONAL ISLAND DETAILS: CC & DID (HOU)
- 59 - 60 DRIVEWAY DETAILS: DD (HOU)
- 61 METAL BEAM GUARD FENCE: GF(31)-14
- 62 METAL BEAM GUARD FENCE TRANSITION: GF(31)TR-14
- 63 SINGLE GUARDRAIL TERMINAL (SKT 350) (WOOD POST): SGT(8)31-14
- 64 SINGLE GUARDRAIL TERMINAL (SKT 351) (STEEL POST): SGT(8)31-14
- 65 SINGLE GUARDRAIL TERMINAL (X-LITE) (STEEL POST): SGT(8)31-14
- 66 RAILROAD CROSSING STOP: END TERMINAL MASH - TL-3T SGT(10)31-16
- 67 MOW STRIP: MS (HOU)
- 68 BRIDGE END DETAILS: BED-14

DRAINAGE DETAILS

- 69 DRAINAGE AREA INDEX MAP
- 70 - 76 DRAINAGE AREA MAP
- 77 - 82 HYDRAULIC DATA SHEET
- 83 - 92 STORM SEWER PLAN AND PROFILE - STORM SEWER TRUNKLINE "NS"
- 93 - 102 STORM SEWER PLAN AND PROFILE - STORM SEWER TRUNKLINE "SS"
- 103 STORM SEWER LATERAL
- 104 - 105 JUNCTION BOX DETAILS
- 106 DETENTION POND LAYOUT
- 107 DETENTION POND CROSS SECTIONS
- 108 DETENTION POND BORING LOGS

SHEET NO.

DESCRIPTION

DRAINAGE DETAILS STANDARDS

- 109 SINGLE BOX CULVERTS PRECAST 3'-0" SPAN: SCP-3
- 110 SINGLE BOX CULVERTS PRECAST 4'-0" SPAN: SCP-4
- 111 SINGLE BOX CULVERTS PRECAST 5'-0" SPAN: SCP-5
- 112 SINGLE BOX CULVERTS PRECAST 6'-0" SPAN: SCP-6
- 113 - 114 SAFETY END TREATMENT: SETP-CD
- 115 SAFETY END TREATMENT: SETP-PD
- 116 PRECAST SAFETY END TREATMENT: PSET-RC
- 117 PRECAST SAFETY END TREATMENT: PSET-RP
- 118 PRECAST SAFETY END TREATMENT: PSET-SC
- 119 PRECAST SAFETY END TREATMENT: PSET-SP
- 120 CURB INLET TYPE C: HIL-C (HOU)
- 121 CURB INLET TYPE C1: HIL-C1 (HOU)
- 122 INLET TYPE A: HIL-A (HOU)
- 123 INLET TYPE B: HIL-B (HOU)
- 124 MISCELLANEOUS SEWER DETAILS: SMD
- 125 GUTTER DEPRESSION DETAILS FOR CURB INLETS: CD (HOU)
- 126 - 127 EXCAVATION AND BACKFILL DIAGRAMS: EBD (HOU)

UTILITIES

EXISTING UTILITIES PLAN & PROFILE

- 128 - 137

SIGNING & PAVEMENT MARKINGS

SIGNING & PAVEMENT MARKING LAYOUTS

- 138 - 142

SIGNING & PAVEMENT MARKINGS STANDARDS

- 143 - 145 TYPICAL SIGN REQUIREMENTS: TSR(3)-13 THRU TSR(5)-13
- 146 DELINEATOR & OBJECT MARKER MATERIAL DESCRIPTION: DROM(1)-15
- 147 DELINEATOR & OBJECT MARKER INSTALLATION: DROM(2)-15
- 148 DELINEATOR & OBJECT MARKER PLACEMENT DETAILS: DROM(3)-15B
- 149 DELINEATOR & OBJECT MARKER PLACEMENT DETAILS: DROM(4)-15
- 150 DELINEATOR & OBJECT MARKER FOR VEHICLE IMPACT ATTENUATORS: DROM(VIA)-15
- 151 TYPICAL STANDARD PAVEMENT MARKINGS: PM(1)-12
- 152 POSITION GUIDANCE USING RAISED MARKERS REFLECTORIZED PROFILE MARKINGS: PM(2)-12
- 153 PAVEMENT MARKINGS FOR TWO-WAY LEFT TURN LANES DIVIDED HIGHWAYS AND RURAL LEFT TURN LANES DIVIDED HIGHWAYS & DETAILS: SMD(GEN)-08
- 154 SIGN MOUNTING DETAILS - SMALL ROADSIDE SIGNS - GENERAL NOTES & DETAILS: SMD(GEN)-08
- 155 - 157 SIGN MOUNTING DETAILS - SMALL ROADSIDE SIGNS - TRIANGULAR SLIP BASE SYSTEM: SMD(SLP)-1 THRU SLP(3)-08

ENVIRONMENTAL ISSUES

- 158 TMDT STORM WATER POLLUTION PREVENTION PLAN (SMP3) (HOU)
- 159 - 164 SMP3 LAYOUT
- 165 - 167 ENVIRONMENTAL PERMITS ISSUES AND COMMITMENTS (EPIC) (HOU)

ENVIRONMENTAL STANDARDS

- 168 TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES
- 169 FENCE & VERTICAL TRACKING: EC(1)-16
- 170 ROCK FILTER DAMS: EC(2)-16
- 171 - 173 TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES
- 174 CONSTRUCTION EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES
- 175 EROSION CONTROL LOGS: EC(9)-16
- 176 FERTILIZER, SEED, SOO, STRAW, COMPOST, AND WATER: (HOU)

CIVILCORP, LLC
FIRM REGISTRATION NUMBER: 10283



THE STANDARD SHEETS SPECIFICALLY IDENTIFIED WITH AN "*" HAVE BEEN SELECTED BY ME OR UNDER MY SUPERVISION AS BEING APPLICABLE TO THIS PROJECT.

Jason C. Kaspar, P.E.
DATE: 11/17/2016

CivilCorp
ENGINEERS - SURVEYORS
1401 W. 42ND STREET, SUITE 1000, FORT WORTH, TEXAS 76103
TEL: 817-335-4100 FAX: 817-335-4100

MISSOURI CITY
TEXAS
DEPARTMENT OF PUBLIC WORKS
SCOTT R. ELMER, P.E., DIRECTOR

TRAMMEL FRESNO ROAD

INDEX OF SHEETS

NO.	STATE	PROJECT NO.	SHEET NO.
6	TEXAS	CS	CS
7	TEXAS	CS	CS
8	TEXAS	CS	CS
9	TEXAS	CS	CS
10	TEXAS	CS	CS
11	TEXAS	CS	CS
12	TEXAS	CS	CS
13	TEXAS	CS	CS
14	TEXAS	CS	CS
15	TEXAS	CS	CS
16	TEXAS	CS	CS
17	TEXAS	CS	CS
18	TEXAS	CS	CS
19	TEXAS	CS	CS
20	TEXAS	CS	CS
21	TEXAS	CS	CS
22	TEXAS	CS	CS
23	TEXAS	CS	CS
24	TEXAS	CS	CS
25	TEXAS	CS	CS
26	TEXAS	CS	CS
27	TEXAS	CS	CS
28	TEXAS	CS	CS
29	TEXAS	CS	CS
30	TEXAS	CS	CS
31	TEXAS	CS	CS
32	TEXAS	CS	CS
33	TEXAS	CS	CS
34	TEXAS	CS	CS
35	TEXAS	CS	CS
36	TEXAS	CS	CS
37	TEXAS	CS	CS
38	TEXAS	CS	CS
39	TEXAS	CS	CS
40	TEXAS	CS	CS
41	TEXAS	CS	CS
42	TEXAS	CS	CS
43	TEXAS	CS	CS
44	TEXAS	CS	CS
45	TEXAS	CS	CS
46	TEXAS	CS	CS
47	TEXAS	CS	CS
48	TEXAS	CS	CS
49	TEXAS	CS	CS
50	TEXAS	CS	CS
51	TEXAS	CS	CS
52	TEXAS	CS	CS
53	TEXAS	CS	CS
54	TEXAS	CS	CS
55	TEXAS	CS	CS
56	TEXAS	CS	CS
57	TEXAS	CS	CS
58	TEXAS	CS	CS
59	TEXAS	CS	CS
60	TEXAS	CS	CS
61	TEXAS	CS	CS
62	TEXAS	CS	CS
63	TEXAS	CS	CS
64	TEXAS	CS	CS
65	TEXAS	CS	CS
66	TEXAS	CS	CS
67	TEXAS	CS	CS
68	TEXAS	CS	CS
69	TEXAS	CS	CS
70	TEXAS	CS	CS
71	TEXAS	CS	CS
72	TEXAS	CS	CS
73	TEXAS	CS	CS
74	TEXAS	CS	CS
75	TEXAS	CS	CS
76	TEXAS	CS	CS
77	TEXAS	CS	CS
78	TEXAS	CS	CS
79	TEXAS	CS	CS
80	TEXAS	CS	CS
81	TEXAS	CS	CS
82	TEXAS	CS	CS
83	TEXAS	CS	CS
84	TEXAS	CS	CS
85	TEXAS	CS	CS
86	TEXAS	CS	CS
87	TEXAS	CS	CS
88	TEXAS	CS	CS
89	TEXAS	CS	CS
90	TEXAS	CS	CS
91	TEXAS	CS	CS
92	TEXAS	CS	CS
93	TEXAS	CS	CS
94	TEXAS	CS	CS
95	TEXAS	CS	CS
96	TEXAS	CS	CS
97	TEXAS	CS	CS
98	TEXAS	CS	CS
99	TEXAS	CS	CS
100	TEXAS	CS	CS

County: Fort Bend

Control: 0912-34-143

Highway: CS

General Notes:

General:

If fixed features require, the governing slopes shown may vary between the limits shown and to the extent determined by the Engineer.

Superelevate the curves to match the existing surface.

Notify the Engineer immediately if discrepancies are discovered in the horizontal control or the benchmark data.

References to manufacturer's trade name or catalog numbers are for the purpose of identification only. Similar materials from other manufacturers are permitted if they are of equal quality, comply with the specifications for this project, and are approved, except for roadway illumination, electrical, and traffic signal items.

The cost for materials, labor, and incidentals to provide for traffic across the roadway and for ingress and egress to private property in accordance with Section 7.2.4 of the standard specifications is subsidiary to the various bid items. Restore access roadways to their original condition upon completing construction.

Grade street intersections and median openings for surface drainage.

If a foundation is to be placed where a riprap surface or an asphalt concrete surface presently exists, use caution in breaking out the existing surface for placement. Break out no greater area than is required to place the foundation. After placing the foundation, wrap the periphery with 0.5 in. pre-molded mastic expansion joint. Then replace the remaining portion of the broken out surface with Class A or Class C concrete or cold mix asphalt concrete to the exact slope, pattern, and thickness of the existing riprap or asphalt. Payment for breaking out the existing surface, wrapping the foundation, and replacing the surface is subsidiary to the various bid items.

Furnish aluminum Type A signs instead of plywood signs for signs shown on the Summary of Small Signs sheet.

Clearly mark or highlight on the shop drawings, the items being furnished for this project. Submit required shop drawings in accordance with the shop drawing distribution list shown in the note for Item 5 for review and distribution.

Right of way parcels or utility adjustments shown to be unclear on the plans but not listed on the special provisions will have no effect on construction.

Unless otherwise shown on the plans or otherwise directed, commence work after sunrise and ensure construction equipment is off the road by sunset.

County: Fort Bend

Control: 0912-34-143 SHEET 8

Highway: CS

Tolls incurred by the Contractor are incidental to the various bid items.

Procure permits and licenses, which are to be issued by the City, County, or Municipal Utility District.

Any groundwater elevation information provided is representative of conditions existing on the day when and for the specific location where this information was collected. The actual groundwater elevation may fluctuate with time, climatic conditions, and construction activity.

REQUIREMENTS OF FORT BEND TOLL ROAD AUTHORITY (FBTRA) FOR WORK NEAR FORT BEND TOLL ROAD

1. All work must meet TxDOT / State of Texas utility accommodation requirements.
2. Notify Phil Martin with FBTRA at least 48 hours prior to commencing work at (713) 574-5261, philmartin@mikestoneassociates.com
3. Contractor shall provide responsible person's name and contract information.
4. Any work in the toll road right of way requires a traffic control plan, even if lanes are not affected. TCP must meet TxDOT or TMUTCD requirements and be reviewed by FBTRA with no objections prior to starting work.
5. Access to Fort Bend Parkway must be coordinated with Phil Martin prior to work.
6. Bore pits within the right of way must be protected during non-work hours.
7. Contractor must clean roadway of dirt and debris prior to end of each work day or prior to opening roadway to traffic.
8. Peak hours are from 5am to 9am, and 3pm to 7pm. No lane closures permitted during peak hours without authorization from FBTRA.
9. Work areas that have been disturbed must be returned to the original condition and may be required to place grass sod and continual watering
10. Upon completion of work, submit CADD/Microstation files and pdf of Record Drawings to Phil Martin with FBTRA.

General: Site Management

Mow the grass and weeds within the project limits a maximum of 3 times a year as directed. This work is subsidiary to the various bid items.

Mark stations every 100 ft. and maintain the markings for the project duration. Remove the station markings at the completion of the project. This work is subsidiary to the various bid items.

Do not mix or store materials, or store or repair equipment, on top of concrete pavement or bridge decks unless authorized by the Engineer. Permission will be granted to store materials on surfaces if no damage or discoloration will result.

Assume ownership of debris and dispose of at an approved location. Do not dispose of debris on private property unless approved in writing by the District Engineer.

County: Fort Bend

Control: 0912-34-143

Highway: CS

Control the dust caused by construction operations. For sweeping the base material in preparation for laying asphalt and for sweeping the finished concrete pavement, use one of the following types of sweepers or approved equal:

Tricycle Type

Wayne Series 900
Elgin White Wing
Elgin Pelican

Truck Type - 4 Wheel

M-B Cruiser II
Wayne Model 945
Mobile TE-3
Mobile TE-4
Murphy 4042

General: Traffic Control and Construction

Schedule construction operations such that preparing individual items of work follows in close sequence to constructing storm drains in order to provide as little inconvenience as practical to the businesses and residents along the project.

Schedule work so that the base placement operations follow the subgrade work as closely as practical to reduce the hazard to the traveling public and to prevent undue delay caused by wet weather.

When design details are not shown on the plans, provide signs and arrows conforming to the latest "Standard Highway Sign Designs for Texas" manual.

General: Utilities

Consider the locations of underground utilities depicted in the plans as approximate and employ responsible care to avoid damaging utility facilities. Depending upon scope and magnitude of planned construction activities, advanced field confirmation by the utility owner or operator may be prudent. Where possible, protect and preserve permanent signs, markers, and designations of underground facilities.

If the Contractor damages or causes damage (breaks, leaks, nicks, dents, gouges, etc.) to the utility, contact the utility facility owner or operator immediately.

At least 48 hours before starting work, make arrangements for locating existing Department-owned above ground and underground fiber optic, communications, power, illumination, and traffic signal cabling and conduit. Do this by calling the Department's Houston District Traffic Signal Operations Office at 713-802-5662 to schedule marking of underground lines on the ground. Use caution if working in these areas to avoid damaging or interfering with existing facilities.

County: Fort Bend

Control: 0912-34-143

SHEET 8A

Highway: CS

Notify the Engineer at least 48 hours before constructing junction boxes at storm drain and utility intersections.

Install or remove poles and luminaires located near overhead or underground electrical lines using established industry and utility safety practices. Consult the appropriate utility company before beginning such work.

If overhead or underground power lines need to be de-energized, contact the electrical service provider to perform this work. Costs associated with de-energizing the power lines or other protective measures required are at no expense to the Department.

If working near power lines, comply with the appropriate sections of Texas State Law and Federal Regulations relating to the type of work involved.

Perform electrical work in conformance with the National Electrical Code (NEC) and Department standard sheets.

Item 5: Control of Work

Before contract letting, electronically generated earthwork cross-section data will be furnished free of charge to the prospective bidders on a compact high-density disk, in an ASCII print format. This will be available through the Association of General Contractors bulletin board service or through the Area Engineer's office. If the earthwork data is not available electronically, reproducible earthwork cross sections are available at the Area Engineer's office for borrowing by copying service companies for the purpose of making copies for the prospective bidders, at the prospective bidder's expense. The earthwork cross-section data provided above is for non-construction purposes only and it is the responsibility of the prospective bidder to validate the enclosed data with the appropriate plans, specifications, and estimates for the projects.

Submit shop drawings electronically for the fabrication of items as documented in Table 1 below. Information and requirements for electronic submittals can be viewed in the "Guide to Electronic Shop Drawing Submittal" which can be accessed through the following web link, http://ftp.dot.state.tx.us/pub/txdot-info/library/pubs/bus/bridge/e_submit_guide.pdf. References to 11 in. x 17 in. sheets in individual specifications for structural items imply electronic CAD sheets.

County: Fort Bend

Control: 0912-34-143

Highway: CS

Table 1
2014 Construction Specification Required Shop/Working Drawing Submittals

Spec Item No.'s	Product	Submittal Required	Approval Required (Y/N)	Contractor/Fabricator P.E. Seal Required	Reviewing Party	Shop or Working Drawing (Note 1)
7.16.1&2	Construction Load Analyses	Y	Y	Y	B	WD
400	Excavation and Backfill for Structures (cofferdams)	Y	N	Y	A	WD
420	Formwork/Falsework	Y	N	Y	A	WD
462	Concrete Box Culvert	Y	Y	N	C	SD
462	Concrete Box Culvert (Alternate Designs Only, calcs req'd.)	Y	Y	Y	B	SD
464	Reinforced Concrete Pipe (Jack and Bore only; ONLY when requested)	Y	Y	Y	A	SD
465	Pre-cast Junction Boxes, Grates, and Inlets	Y	Y	N	A	SD
465	Pre-cast Junction Boxes, Grates, and Inlets (Alternate Designs Only, calcs req'd.)	Y	Y	Y	B	SD
467	Pre-cast Safety End Treatments	Y	Y	N	A	SD

Notes:

- Document flow for Working Drawings differs from Shop Drawings in that Working Drawings must be submitted to the Engineer rather than the Engineer of Record and they are for the information of the Engineer only; an approval stamp and distribution to all project offices is not required.

Key to Reviewing Party

A - Area Office	
Area Office	Email Address
Fort Bend Area Office	HOU-FBAShpDrwgs@txdot.gov
B - Houston Bridge Engineer	
Bridge Design (Houston TxDOT)	HOU-BrqShpDrwgs@txdot.gov
BRG - Austin Bridge Division	
Bridge Design (Austin TxDOT)	BRG_ShopPlanReview@txdot.gov
C - Construction Office	
Construction	HOU-ConstrShpDrwgs@txdot.gov
Laboratory	HOU-LabShpDrwgs@txdot.gov

Item 7: Legal Relations and Responsibilities

The Contractor Force Account "Safety Contingency" that has been established for this project is intended to be utilized for work zone enhancements, to improve the effectiveness of the Traffic Control Plan, that could not be foreseen in the project planning and design stage. These enhancements will be mutually agreed upon by the Engineer and the Contractor's Responsible Person based on weekly or more frequent traffic management reviews on the project. The Engineer may choose to use existing bid items if it does not slow the implementation of enhancement.

County: Fort Bend

Control: 0912-34-143

SHEET 8B

Highway: CS

Do not initiate activities in a Project Specific Location (PSL), associated with a U.S. Army Corps of Engineers (USACE) permit area, that have not been previously evaluated by the USACE as part of the permit review of this project. Such activities include those pertaining to, but are not limited to, haul roads, equipment staging areas, borrow and disposal sites. Associated defined here means materials are delivered to or from the PSL. The permit area includes the waters of the U.S. or associated wetlands affected by activities associated with this project. Special restrictions may be required for such work. Assume responsibility for consultations with the USACE regarding activities, including PSLs that have not been previously evaluated by the USACE. Provide the Department with a copy of consultations or approvals from the USACE before initiating activities.

The Contractor may proceed with activities in PSLs that do not affect a USACE permit area if a self-determination has been made that the PSL is non-jurisdictional or if proper USACE clearances have been obtained in jurisdictional areas or have been previously evaluated by the USACE as part of the permit review of this project. The Contractor is solely responsible for documenting any determinations that their activities do not affect a USACE permit area. Maintain copies of their determinations for review by the Department or any regulatory agency. Document and coordinate with the USACE, if required, before hauling any excavation from or hauling any embankment to a USACE permit area by either 1 or 2 below:

1. Restricted Use of Materials for the Previously Evaluated Permit Areas.

Document both the Project Specific Locations (PSL) and their authorization. Maintain copies for review by the Department or any regulatory agency. When an area within the project limits has been evaluated by the USACE as part of the permit process for this project:

- Suitable excavation of required material in the areas shown on the plans and cross sections as specified in the Item, "Excavation" is used for permanent or temporary fill (under the Item, "Embankment") within a USACE permit area.
- Suitable embankment (under the Item, "Embankment") from within the USACE permit area is used as fill within a USACE evaluated area.
- Unsuitable excavation or excess excavation, "Waste" (under the Item, "Excavation"), that is disposed of at a location approved within a USACE evaluated area.

2. Contractor Materials from Areas Other than Previously Evaluated Areas.

Provide the Department with a copy of USACE coordination or approvals before initiating any activities for an area within the project limits that has not been evaluated by the USACE or for any off right of way locations used for the following, but not limited to, haul roads, equipment staging areas, borrow and disposal sites:

- The Item, "Embankment" used for temporary or permanent fill within a USACE permit area.
- Unsuitable excavation or excess excavation, "Waste" (under the Item, "Excavation"), that is disposed of outside a USACE evaluated area.

County: Fort Bend

Control: 0912-34-143

Highway: CS

The total area disturbed for this project is 6.28 acres. The disturbed area in this project, the project locations in the Contract, and Contractor project specific locations (PSLs) within 1 mile of the project limits for the Contract, will further establish the authorization requirements for storm water discharges. The Department will obtain an authorization to discharge storm water from the Texas Commission on Environmental Quality (TCEQ) for the construction activities shown on the plans. The Contractor is to obtain required authorization from the TCEQ for Contractor PSLs for construction support activities on or off the ROW. When the total area disturbed in the Contract and PSLs within 1 mile of the project limits exceeds 5 acres, provide a copy of the Contractor NOI for PSLs on the ROW to the Engineer (to the appropriate MS4 operator when on an off-state system route) and to the local government that operates a separate storm drain system.

This project does not require a U.S. Army Corps of Engineers (USACE) Section 404 Permit before letting, but if a permit is needed during construction, assume responsibility for preparing the permit application. Submit the permit application to the Department's District Environmental Section for approval. Once the permit application is approved, the Department will submit it to the USACE. Assume responsibility for the requested revisions, in coordination with the Department's District Environmental Section.

Maintain the roadway slope stability. Maintaining slope stability is subsidiary to the various bid items.

The nesting / breeding season for migratory birds is March 1 through August 30.

Conduct any tree removal outside of the migratory bird nesting season. If this is not possible due to scheduling, then exercise caution to remove only those trees with no active nests. Do not destroy nests on structures or in trees within the project limits during the nesting / breeding season.

Take measures to prevent the building of nests on any structures or trees within the project limits throughout the duration of the construction if work / removal will be performed during the nesting / breeding season. This can be accomplished by application of bird repellent gel, netting by hand every 3 to 4 days, or any other non-threatening method approved by the Houston District Environmental Section. Obtain this approval well in advance of the planned use. Contact the Houston District Environmental Section at 713-802-5244. The cost of this work is subsidiary to the various bid items.

Item 8: Prosecution and Progress

The Department will not adjust the number of days for the project and milestones, if any, due to differences in opinion regarding any assumptions made in the preparation of the schedule or for errors, omissions, or discrepancies found in the time determination schedule.

County: Fort Bend

Control: 0912-34-143

Highway: CS

Working days will be computed and charged based on a *standard* workweek in accordance with Section 8.3.1.4

The maximum number of days the time charges on this contract may be suspended due to contractor mobilization, and material fabrication/accumulation or processing delays is 60 days. The Engineer and the Contractor may mutually agree, in writing, to increase or decrease this maximum number of days.

Item 100: Preparing Right of Way

The Item, "Preparing Right of Way" will be measured for payment only in those designated areas shown on the plans. Preparing right of way necessary to perform construction that is outside designated areas is subsidiary to this bid Item.

Remove abandoned utilities that are in conflict with the new utilities, at no expense to the Department.

Reestablish and maintain right of way stakes after completing the right of way preparation activities and until the new utilities are in place.

Remove and assume ownership of the existing ground mounted signs within the limits of roadway construction unless otherwise noted or directed. This work is subsidiary to the Item, "Preparing Right of Way."

Item 104: Removing Concrete

Removing concrete curb is paid as a separate bid item if the existing pavement on which it rests is not removed at the same time.

Item 105: Removing Treated and Untreated Base and Asphalt Pavement Item 305: Salvaging, Hauling, and Stockpiling Reclaimable Asphalt Pavement

Case 1 - ACP over asphalt treatment

Removing the Asphalt Concrete Pavement (ACP) and the asphalt treatment/asphalt stabilized base are paid for under the Item, "Salvaging, Hauling, and Stockpiling Reclaimable Asphalt Pavement."

Removing the cement or lime treatment is paid under the Item, "Removing Treated and Untreated Base and Asphalt Pavement."

Remove the ACP separately from the asphalt treatment/asphalt stabilized base. Make the removed depth as uniform as possible during each removal pass if the pavement depth being removed is composed of different asphalt layers. Unless otherwise approved, stockpile Reclaimable Asphalt Pavement (RAP) of differing types of quality separately by its intended use such as for the asphalt treatment, cement treatment, lime treatment, or asphalt concrete pavement. Break, crush, or mill the stockpiled materials so that 100 percent pass the 2-in. sieve.

County: Fort Bend

Control: 0912-34-143

Highway: CS

Obtain a secured site for the stockpile of the treated material to be salvaged from this project. Haul and stockpile the unused material as directed. This work is subsidiary to this bid item.

Item 110: Excavation

If manipulating the excavated material requires moving the same material more than once to accomplish the desired results, the excavation is measured and paid for only once regardless of the manipulation required.

Transition the ditch grades and channel bottom widths at structure locations. Use only approved channel excavation in the embankment.

The total excavation quantity shown on the plans includes the quantity for excavating to 2 ft. behind the back of the proposed curb.

Item 132: Embankment

If salvaged base is used for the embankment material, break it into small pieces to achieve the required density and to facilitate placing in the embankment. Obtain approval of the material before placing in the embankment.

Furnish Type C material with a maximum Liquid Limit (LL) of 65, a minimum Plasticity Index (PI) of 5, and composed of suitable earth material such as loam, clay, or other materials that form a suitable embankment.

The embankment material used on the project which has a Liquid Limit exceeding 45 will be tested for Liquid Limits at the rate of one test per 20,000 cu. yd. or per total quantity less than 20,000 cu. yd., unless otherwise directed. Only use material that passes the above tests.

Provide a finished grade with the top 4 in. capable of sustaining vegetation. Use fertile soil that is easily cultivated, free from objectionable material and highly resistant to erosion.

Item 161: Compost

Item 162: Sodding for Erosion Control

Item 164: Seeding for Erosion Control

Item 166: Fertilizer

Item 168: Vegetative Watering

Refer to the "Fertilizer, Seed, Sod, Straw, Compost, and Water" plan sheet for material specifications, application rates, and for watering requirements.

Item 204: Sprinkling

Perform subsidiary sprinkling as required under various other items in accordance with the Item, "Sprinkling."

Sprinkling for dust control is subsidiary to the various bid items.

County: Fort Bend

Control: 0912-34-143

Highway: CS

Item 260: Lime Treatment (Road-Mixed)

For slurry placing, before discharging through the distributors, sufficiently agitate or mix the lime and water to place the lime in suspension and to obtain a uniform mixture.

The Engineer will observe the lime treatment that the Contractor elects to open to construction traffic immediately after compaction. If the construction traffic damages the subgrade, route the traffic off the damaged section in accordance with the standard specification. If the construction traffic does not damage the subgrade, cure the subgrade until other courses of material cover it. Apply these courses within 14 days with a maximum curing period of 7 days.

Place the hydrated and the commercial lime as a water suspension or slurry according to the slurry placing method shown in Section 260.4.3.2, "Slurry Placement."

Use the type of lime at particular locations as directed.

Place the quicklime dry or as a slurry.

For the dry quicklime, a spreader box is not required if the lime material is evenly distributed.

In limited areas, the Contractor may construct the lime slurry subgrade under a sequence of work in which the application, mixing, and compaction are completed in the same working day, if approved by the Engineer.

Provide documentation from certified public scales showing gross, tare, and net weights. Provide producer's delivery tickets also showing gross, tare, and net weights. Completely empty the lime trailers at the project site. The Engineer may direct the Contractor to reweigh any shipment of lime on certified scales. The cost of this operation is subsidiary to the Item, "Lime Treatment (Road-Mixed)."

The percentage of lime shown on the plans is estimated on the basis of engineering tests. If soil tests made during construction indicate properties different than those originally anticipated, the Engineer may vary the percentage of the lime to provide soil characteristics similar to those of the preliminary tests.

Mix the lime with the new base material in an approved pug mill type stationary mixer.

Item 305: Salvaging, Hauling, and Stockpiling Reclaimable Asphalt Pavement

Unless otherwise shown on the plans, RAP generated by this project will become the property of the Contractor for use in the current construction project or in future projects.

Keep the removed depth as uniform as possible during each removal pass if the pavement depth being removed is composed of different asphalt layers. Stockpile the RAP of differing types of quality separately by its intended use such as for asphalt treatment, cement treatment, lime treatment, or asphalt concrete pavement (level up). Break, crush, or mill the stockpiled materials so that 100 percent passes the 2-in. sieve.

County: Fort Bend

Control: 0912-34-143

Highway: CS

Verify the depth of asphalt pavement to be removed before beginning the removal.

Item 360: Concrete Pavement

Where the pavement curb is left off for a later tie, provide the dowels or the tie bars as indicated on the paving detail sheets. The dowel bars and tie bars are subsidiary to the various bid items.

Repair portions of the concrete pavement surfaces that are damaged while in a plastic state before that area receives permanent pavement markings and opens to traffic. Perform repairs that are structurally equivalent to and cosmetically uniform with the adjacent undamaged areas. Do not repair by grouting onto the surface.

On pavement widening, hand finishing in place of the longitudinal float will be permitted.

Where existing pavement is widened with new pavement, place the new pavement a minimum of 2 ft. wide.

Equip the batching plants to proportion by weight, aggregates and bulk cement, using approved proportioning devices and approved automatic scales.

For mono curb, the curb height transitions will be paid at the contract unit price of the larger curb height in the transition. The 2.5-in. laydown curbs for driveways will be paid at the unit price bid for the Item, "Conc Curb (Mono) (Ty II)."

High-early strength cement may be used for frontage road and city street intersection construction.

Do not use limestone dust or fracture as fine aggregate.

If the concrete design requires greater than 5.5 sacks of cementitious material per cubic yard, obtain written approval. If placing concrete pavement mixes from April 1 to October 31, inclusive, use Mix Design Option 1 as specified in Section 421.4.2.6.1..

Perform saw cutting as shown on the plans in accordance with Section 360.4.10, "Sawing Joints." This saw cutting is subsidiary to this bid item.

Items 360, 420, and 421: All Concrete Items

For the Department's concrete cylinder split samples, transport the test cylinders to the Houston District Laboratory located at 7600 Washington Avenue in Houston, or to the appropriate Area Laboratory, when applicable. Transporting the test cylinders is subsidiary to the various bid items.

Item 400: Excavation and Backfill for Structures

Plugging existing pipe culverts is subsidiary to the various bid items.

County: Fort Bend

Control: 0912-34-143

SHEET 8E

Highway: CS

If Recycled Cement Treatment (Type D) is included in the plans, the following additional requirements apply:

1. Use only approved sand, crushed concrete, or salvaged base free from deleterious matter, as aggregate for cement-stabilized backfill.
2. Provide crushed concrete or salvaged base backfill material in accordance with the Item, "Cement Treatment (Plant-Mixed)(Type D)" (base or crushed concrete), except the recycled Type D material must not contain Reclaimed Asphalt Pavement (RAP).
3. For backfill material below the spring line of pipes, use cement-stabilized sand rather than Recycled Type D backfill material.
4. For the cement-stabilized sand backfill, use a minimum of 7 percent of hydraulic cement based on the dry weight of backfill material. The cement content for the crushed concrete and salvaged base is specified in the Item, "Cement Treatment (Plant-Mixed) (Type D)."
5. Place and compact the stabilized backfill material using a gradation that provides a dense mass without segregating and is impervious to passing of water.

Item 421: Hydraulic Cement Concrete

Entrained air is required in all slip formed concrete (bridge rail, concrete traffic barrier, pavement, etc.), but is not required for other structural concrete. Adjust the dosage of air entraining agent for low air content as directed or allowed by the Engineer. If entrained air is provided where not required, do not exceed the manufacturer's recommended dosage.

Item 462: Concrete Box Culverts and Drains

Item 464: Reinforced Concrete Pipe

Concrete collars are subsidiary to the various bid items except for those specified on the plans for stage construction, which are paid for under the Item, "Concrete Substructures" as "C1 C Conc (Collar)."

Rubber gaskets are required for concrete pipe joints except for connections of safety end treatments, driveway culverts, and joints between the existing pipes and extensions.

If performing the work under the Item, "Jacking, Boring, or Tunneling Pipe or Box," use tongue and groove pipe instead of rubber gaskets at these locations.

Open, install, and backfill each section, or a portion of a section, in the same day at locations requiring pipe culverts under existing roadways.

Place the pipe drains across existing roadways half at a time to allow passage of traffic. No trenches may remain open overnight.

County: Fort Bend

Control: 0912-34-143

Highway: CS

Known locations of existing stub-outs are shown on the plans, but these stub-outs may be in a different position or condition. Delays, inconveniences, or additional work required will not be a basis for additional compensation.

Provide leave-outs or holes in the proposed storm drain structures and pipes for drainage during interim construction. This work is subsidiary to the various bid items.

The flowline elevations of side road structures are based on the proposed ditches. Field-verify these elevations and adjust them as necessary to meet the field conditions. Before placing these structures, prepare and submit for approval, the data (revised elevation, alignment, length, etc.) for the adjusted structures.

If groundwater is encountered while installing the storm drain system, install a suitable dewatering system to facilitate construction of the storm drains. The costs for materials and labor required to install and maintain this system are subsidiary to the Item, "Reinforced Concrete Pipe."

Item 465: Junction Boxes, Manholes, and Inlets

If required on the plans, build manholes and inlets to stage 1 construction, cover with temporary pavement, and complete in a later phase of construction. This temporary covering and pavement are subsidiary to the various bid items.

Construct manholes and inlets in graded areas, first to an elevation at least 4 in. above the top of the highest entering pipe and cover with a wooden cover. Complete the construction of such manholes and inlets to the finished elevation when completing the grading work for such manholes and inlets. Adjust the final elevation, if required, since this elevation is approximate.

Construct manholes and inlets in paved areas to an elevation so their temporary wooden covers are flush with the surface of the base material.

Do not leave excavations or trenches open overnight.

Item 502: Barricades, Signs, and Traffic Handling

Use a traffic control plan for handling traffic through the various phases of construction. Follow the phasing sequence unless otherwise agreed upon by the Area Engineer and the Project Manager. Ensure this plan conforms to the latest "Texas Manual on Uniform Traffic Control Devices" and the latest Barricade and Construction (BC) Standard Sheets. Submit changes to the traffic control plan to the Area Engineer. Provide a layout showing the construction phasing, signs, striping, and signalizations for changes to the original traffic control plan.

Furnish and maintain the barricades and warning signs, including the necessary temporary and portable traffic control devices, during the various phases of construction. Place and construct these barricades and warning signs in accordance with the latest "Texas Manual on Uniform Traffic Control Devices" for typical construction layouts.

County: Fort Bend

Control: 0912-34-143 SHEET 8F

Highway: CS

Cover work zone signs when work related to the signs is not in progress, or when any hazard related to the signs no longer exists.

Keep the delineation devices, signs, and pavement markings clean. This work is subsidiary to the Item, "Barricades, Signs, and Traffic Handling."

Cover or remove the permanent signs and construction signs that are incorrect or that do not apply to the current situation for a particular phase.

Do not mount signs on drums or barricades, except those listed in the latest Barricades and Construction standard sheets.

Use traffic cones for daytime work only. Replace the cones with plastic drums during nighttime hours.

Place positive barriers to protect drop-off conditions greater than 2 ft. within the clear zone that remain overnight.

Use shadow vehicles with Truck Mounted Attenuators (TMA) for lane and shoulder closures. A minimum of 7 days in advance of any total closure, notify the Houston District Public Information Office of which roadways, ramps, intersections, or lanes will be closed, the dates they will remain closed, and when they will be opened again to traffic.

Item 504: Field Office and Laboratory

Furnish one Type A structure for the laboratory. Ensure the windows for the structure have burglar bars.

Item 506: Temporary Erosion, Sedimentation and Environmental Controls

A Storm Water Pollution Prevention Plan (SWP3) is required. Since the disturbed area is more than 5 acres, a "Notice of Intent" (NOI) is also required.

Use appropriate measures to prevent, minimize, and control the spill of hazardous materials in the construction staging area. Remove and dispose of materials in compliance with State and Federal laws.

Before starting construction, review with the Engineer the SWP3 used for temporary erosion control as outlined on the plans. Before construction, place the temporary erosion and sedimentation control features as shown on the SWP3.

Schedule the seeding or sodding work as soon as possible. The project schedule provides for a vegetation management plan.

County: Fort Bend

Control: 0912-34-143

Highway: CS

After completing earthwork operations, restore and reseed the disturbed areas in accordance with the Department's specifications for permanent or temporary erosion control.

Implement temporary and permanent erosion control measures to comply with the National Pollution Discharge Elimination System (NPDES) general permit under the Clean Water Act.

Before starting grading operations and during the project duration, place the temporary or permanent erosion control measures to prevent sediment from leaving the right of way.

Item 529: Concrete Curb, Gutter, and Combined Curb and Gutter

Item 530: Intersections, Driveways, and Turnouts

Item 531: Sidewalks

An air-entraining admixture is not required.

For concrete curbs, use Grade 7 aggregate conforming to Section 421.2.6 of the Item, "Hydraulic Cement Concrete."

For driveways and turnouts, coarse aggregate Grade No. 3 through No. 8 conforming to the gradation requirements specified in the Item, "Hydraulic Cement Concrete" will be permitted.

For reinforcing steel in sidewalks and pedestrian ramps, use No. 4 bars at a maximum 18 in. spacing center-to-center in both directions.

Item 540: Metal Beam Guard Fence

Painting the timber posts is not required.

Use timber posts for galvanized steel metal beam guard fence, except for anchorage at turned down ends.

Furnish and install wood blocks between the rail elements and the timber posts as detailed on the plans. These block-outs are subsidiary to this bid Item.

The quantity of the metal beam guard fence is subject to change.

Provide a mow strip as shown on the plans, at metal beam guard fence locations, including any guardrail end treatments.

Galvanize the rail elements supplied for this project by using a Type II Zinc Coating.

Item 542: Removing Metal Beam Guard Fence

Accept ownership and property dispose of removed metal beam guard fence and terminal anchor in accordance with federal, state and local regulations.

County: Fort Bend

Control: 0912-34-143 SHEET 8G

Highway: CS

Item 585: Ride Quality for Pavement Surfaces

To eliminate the need for corrective action due to excessive deviations in the final surface layers, exercise caution to ensure satisfactory profile results in the intermediate paving layers (mixture).

For Jointed Reinforced Concrete Pavement (JRCp), use Surface Test Type A.

Item 644: Small Roadside Sign Assemblies

Sign locations shown on the plans are approximate. Before placing them, obtain approval of and then stake the exact locations for these signs.

Use the Texas Universal Triangular Slip Base with the concrete foundation for small ground mounted signs, unless otherwise shown in the plans.

Remove existing street name signs from existing stop signs and re-install them above the new stop signs. Removing and re-installing existing street name signs is subsidiary to the Item, "Small Roadside Sign Assemblies."

When design details are not shown on the plans, provide signs and arrows conforming to the latest "Standard Highway Sign Designs for Texas" manual.

Use Type E Super High Specific Intensity (Fluorescent Prismatic) yellow green reflective sheeting background to fabricate school signs (S1-1, S3-1, S4-3, S5-1, W16-2, SW16-9p, and SW16-7pL(R)).

Assume ownership of the removed existing signs.

Locations of the relocated signs are approximate. Before placing them, obtain approval of and then stake the exact locations for these signs.

Replace existing signs that become damaged during relocation at no expense to the Department.

Item 666: Reflectorized Pavement Markings

Use Type III glass beads for thermoplastic pavement markings.

Use a 0.100 in. (100 mil) thickness for thermoplastic pavement markings, measured to the top of the thermoplastic, not including the exposed glass beads.

If the Type II markings become dirty and require cleaning by washing, brushing, compressed air, or other approved methods before applying the Type I thermoplastic markings, this additional cleaning is subsidiary to the Item, "Reflectorized Pavement Markings."

Establish the alignment and layout for work zone striping and permanent striping.

County: Fort Bend

Control: 0912-34-143

SHEET 8H

Highway: CS

Stripe all roadways before opening them to traffic.

Place pavement markings under these items in accordance with details shown on the plans, the latest "Texas Manual on Uniform Traffic Control Devices," or as directed.

When design details are not shown on the plans, provide pavement markings for arrows, words, and symbols conforming to the latest "Standard Highway Sign Designs for Texas" manual.

Item 672: Raised Pavement Markers

If other operations are complete on the project and if the curing time period is not yet elapsed, the contract time will be suspended until the curing is done.

Before placing the raised pavement markers on concrete pavement, blast clean the surface using an abrasive-blasting medium. This work is subsidiary to the Item, "Raised Pavement Markers."

Provide epoxy adhesive that is machine-mixed or nozzle-mixed and dispensed. Equip the machine or nozzle with a mechanism to ensure positive mix measurement control.

Item 677: Eliminating Existing Pavement Markings and Markers

Remove existing pavement markings on concrete or asphalt surfaces by flail milling or as directed.

Item 678: Pavement Surface Preparation for Markings

On new concrete pavement or on existing concrete pavement when placing a new stripe on a new location, remove the curing compounds and contamination from the pavement surface by flail milling or as directed. In addition, air-blast the surface with compressed air just before placing the new stripe.


On existing concrete pavement when placing a new stripe on an existing location, after removing the existing stripe under the Item, "Eliminating Existing Pavement Markings and Markers," air-blast the surface with compressed air just before placing the new stripe.

Do not clean concrete pavement by grinding.

Basis of Estimate

Item	Description	Limit and Rate	Unit
260	Lime Treatment (Road-Mixed) For materials used as subgrade *		SY
	• Lime(HYD, COM, or QK)(SLRY) or QK(DRY)	6 % by weight based on 100 Lb. / Cu. Ft. subgrade	TON

* If used in existing roadway base, rate will be determined on a case by case basis.



NOTES

1. SEE TRAFFIC CONTROL PLAN STANDARDS FOR SIGN, FLAG, OR CONE PLACEMENT, ADVANCED WARNING AND DEVICE SPACING.
2. CONTRACTOR TO MAINTAIN INGRESS & EGRESS TO MAD 48 WASTEWATER TREATMENT PLANT ENTRANCE (STA 29+92) THROUGHOUT CONSTRUCTION.
3. IN LIEU OF JACK & BORE, CONTRACTOR MAY UTILIZE TCE (11-21-12) TO CONSTRUCT CULVERT ACROSS TRAMMEL FRESNO ROAD.

0 400' 800'
 SCALE: 1" = 800'

CIVILCORP, LLC
 FIRM REGISTRATION NUMBER: 10263
 JASON C. KASPER
 108672
 11/11/2016

CivilCorp
 ANNA WILKINS, INC., SUITE 400, JOHNSON, TEXAS 77030
 TEL: 281-291-2200 FAX: 281-291-2201
 WWW.CIVILCORP.COM

MISSOURI CITY
 TEXAS
 DEPARTMENT OF PUBLIC WORKS
 SCOTT R. ELKER, P.E. - DIRECTOR

TRAMMEL FRESNO ROAD
 DETOUR LAYOUT

HSR	STATE	PROJECT NO.	HPF NO.
6	TEXAS		CS
APR	COUNTY	CONTRACT	SECTION
101	FORT BEND	0912	34 143
			SHEET NO.
			18


1. The Barrier and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
2. The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
3. The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
4. The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
5. Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO) "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
6. When projects start, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor should erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
7. The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
8. All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
9. The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
10. As shown on BC(2), the OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER (see Sign Detail G20-10T) and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. However, the TRAFFIC FINES DOUBLE sign will not be required on projects consisting solely of mobile operation work, such as striping or milling/edgeline rumble strips. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits.
11. Except for devices required by Note 10, traffic control devices should be in place only while work is actually in progress or a definite need exists.
12. The Engineer has the final decision on the location of all traffic control devices.
13. Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

WORKER SAFETY APPAREL NOTES:

Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic or work areas or night time work.

WORKER SAFETY APPAREL NOTES:

Workers on night who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISFA American National Standard for High-Visibility Apparel, or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.




Only pre-qualified products shall be used. The "Compilant Work Zone Traffic Control Devices List" (CWZTC) describes pre-qualified products and their sources and may be found on-line at the web address given below or by contacting:

Texas Department of Transportation
Traffic Operations Division - TE
Phone (512) 416-3118

THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT
<http://www.txdot.gov>


COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTD)
DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
MATERIAL PRODUCER LIST (MPL)
ROADWAY DESIGN MANUAL - SEE "MANUALS (ON-LINE MANUALS)"
STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
TRAFFIC ENGINEERING STANDARD SHEETS

 Texas Department of Transportation		Traffic Operations Manual Standard
<h1 style="text-align: center;">BARRICADE AND CONSTRUCTION GENERAL NOTES AND REQUIREMENTS</h1>		
<h2 style="text-align: center;">BC(1) -14</h2>		
TITLE: BC(1) -14 DATE: 11/01/00 REVISIONS: 4-03 5-10 8-14 9-07 7-13	Item 13001 Item 13021 Item 1413 Item 1414 Item 1415 Item 1416 Item 1417 Item 1418 Item 1419 Item 1420 Item 1421 Item 1422 Item 1423 Item 1424 Item 1425 Item 1426 Item 1427 Item 1428 Item 1429 Item 1430 Item 1431 Item 1432 Item 1433 Item 1434 Item 1435 Item 1436 Item 1437 Item 1438 Item 1439 Item 1440 Item 1441 Item 1442 Item 1443 Item 1444 Item 1445 Item 1446 Item 1447 Item 1448 Item 1449 Item 1450 Item 1451 Item 1452 Item 1453 Item 1454 Item 1455 Item 1456 Item 1457 Item 1458 Item 1459 Item 1460 Item 1461 Item 1462 Item 1463 Item 1464 Item 1465 Item 1466 Item 1467 Item 1468 Item 1469 Item 1470 Item 1471 Item 1472 Item 1473 Item 1474 Item 1475 Item 1476 Item 1477 Item 1478 Item 1479 Item 1480 Item 1481 Item 1482 Item 1483 Item 1484 Item 1485 Item 1486 Item 1487 Item 1488 Item 1489 Item 1490 Item 1491 Item 1492 Item 1493 Item 1494 Item 1495 Item 1496 Item 1497 Item 1498 Item 1499 Item 1500 Item 1501 Item 1502 Item 1503 Item 1504 Item 1505 Item 1506 Item 1507 Item 1508 Item 1509 Item 1510 Item 1511 Item 1512 Item 1513 Item 1514 Item 1515 Item 1516 Item 1517 Item 1518 Item 1519 Item 1520 Item 1521 Item 1522 Item 1523 Item 1524 Item 1525 Item 1526 Item 1527 Item 1528 Item 1529 Item 1530 Item 1531 Item 1532 Item 1533 Item 1534 Item 1535 Item 1536 Item 1537 Item 1538 Item 1539 Item 1540 Item 1541 Item 1542 Item 1543 Item 1544 Item 1545 Item 1546 Item 1547 Item 1548 Item 1549 Item 1550 Item 1551 Item 1552 Item 1553 Item 1554 Item 1555 Item 1556 Item 1557 Item 1558 Item 1559 Item 1560 Item 1561 Item 1562 Item 1563 Item 1564 Item 1565 Item 1566 Item 1567 Item 1568 Item 1569 Item 1570 Item 1571 Item 1572 Item 1573 Item 1574 Item 1575 Item 1576 Item 1577 Item 1578 Item 1579 Item 1580 Item 1581 Item 1582 Item 1583 Item 1584 Item 1585 Item 1586 Item 1587 Item 1588 Item 1589 Item 1590 Item 1591 Item 1592 Item 1593 Item 1594 Item 1595 Item 1596 Item 1597 Item 1598 Item 1599 Item 1600 Item 1601 Item 1602 Item 1603 Item 1604 Item 1605 Item 1606 Item 1607 Item 1608 Item 1609 Item 1610 Item 1611 Item 1612 Item 1613 Item 1614 Item 1615 Item 1616 Item 1617 Item 1618 Item 1619 Item 1620 Item 1621 Item 1622 Item 1623 Item 1624 Item 1625 Item 1626 Item 1627 Item 1628 Item 1629 Item 1630 Item 1631 Item 1632 Item 1633 Item 1634 Item 1635 Item 1636 Item 1637 Item 1638 Item 1639 Item 1640 Item 1641 Item 1642 Item 1643 Item 1644 Item 1645 Item 1646 Item 1647 Item 1648 Item 1649 Item 1650 Item 1651 Item 1652 Item 1653 Item 1654 Item 1655 Item 1656 Item 1657 Item 1658 Item 1659 Item 1660 Item 1661 Item 1662 Item 1663 Item 1664 Item 1665 Item 1666 Item 1667 Item 1668 Item 1669 Item 1670 Item 1671 Item 1672 Item 1673 Item 1674 Item 1675 Item 1676 Item 1677 Item 1678 Item 1679 Item 1680 Item 1681 Item 1682 Item 1683 Item 1684 Item 1685 Item 1686 Item 1687 Item 1688 Item 1689 Item 1690 Item 1691 Item 1692 Item 1693 Item 1694 Item 1695 Item 1696 Item 1697 Item 1698 Item 1699 Item 1700 Item 1701 Item 1702 Item 1703 Item 1704 Item 1705 Item 1706 Item 1707 Item 1708 Item 1709 Item 1710 Item 1711 Item 1712 Item 1713 Item 1714 Item 1715 Item 1716 Item 1717 Item 1718 Item 1719 Item 1720 Item 1721 Item 1722 Item 1723 Item 1724 Item 1725 Item 1726 Item 1727 Item 1728 Item 1729 Item 1730 Item 1731 Item 1732 Item 1733 Item 1734 Item 1735 Item 1736 Item 1737 Item 1738 Item 1739 Item 1740 Item 1741 Item 1742 Item 1743 Item 1744 Item 1745 Item 1746 Item 1747 Item 1748 Item 1749 Item 1750 Item 1751 Item 1752 Item 1753 Item 1754 Item 1755 Item 1756 Item 1757 Item 1758 Item 1759 Item 1760 Item 1761 Item 1762 Item 1763 Item 1764 Item 1765 Item 1766 Item 1767 Item 1768 Item 1769 Item 1770 Item 1771 Item 1772 Item 1773 Item 1774 Item 1775 Item 1776 Item 1777 Item 1778 Item 1779 Item 1780 Item 1781 Item 1782 Item 1783 Item 1784 Item 1785 Item 1786 Item 1787 Item 1788 Item 1789 Item 1790 Item 1791 Item 1792 Item 1793 Item 1794 Item 1795 Item 1796 Item 1797 Item 1798 Item 1799 Item 1800 Item 1801 Item 1802 Item 1803 Item 1804 Item 1805 Item 1806 Item 1807 Item 1808 Item 1809 Item 1810 Item 1811 Item 1812 Item 1813 Item 1814 Item 1815 Item 1816 Item 1817 Item 1818 Item 1819 Item 1820 Item 1821 Item 1822 Item 1823 Item 1824 Item 1825 Item 1826 Item 1827 Item 1828 Item 1829 Item 1830 Item 1831 Item 1832 Item 1833 Item 1834 Item 1835 Item 1836 Item 1837 Item 1838 Item 1839 Item 1840 Item 1841 Item 1842 Item 1843 Item 1844 Item 1845 Item 1846 Item 1847 Item 1848 Item 1849 Item 1850 Item 1851 Item 1852 Item 1853 Item 1854 Item 1855 Item 1856 Item 1857 Item 1858 Item 1859 Item 1860 Item 1861 Item 1862 Item 1863 Item 1864 Item 1865 Item 1866 Item 1867 Item 1868 Item 1869 Item 1870 Item 1871 Item 1872 Item 1873 Item 1874 Item 1875 Item 1876 Item 1877 Item 1878 Item 1879 Item 1880 Item 1881 Item 1882 Item 1883 Item 1884 Item 1885 Item 1886 Item 1887 Item 1888 Item 1889 Item 1890 Item 1891 Item 1892 Item 1893 Item 1894 Item 1895 Item 1896 Item 1897 Item 1898 Item 1899 Item 1900 Item 1901 Item 1902 Item 1903 Item 1904 Item 1905 Item 1906 Item 1907 Item 1908 Item 1909 Item 1910 Item 1911 Item 1912 Item 1913 Item 1914 Item 1915 Item 1916 Item 1917 Item 1918 Item 1919 Item 1920 Item 1921 Item 1922 Item 1923 Item 1924 Item 1925 Item 1926 Item 1927 Item 1928 Item 1929 Item 1930 Item 1931 Item 1932 Item 1933 Item 1934 Item 1935 Item 1936 Item 1937 Item 1938 Item 1939 Item 1940 Item 1941 Item 1942 Item 1943 Item 1944 Item 1945 Item 1946 Item 1947 Item 1948 Item 1949 Item 1950 Item 1951 Item 1952 Item 1953 Item 1954 Item 1955 Item 1956 Item 1957 Item 1958 Item 1959 Item 1960 Item 1961 Item 1962 Item 1963 Item 1964 Item 1965 Item 1966 Item 1967 Item 1968 Item 1969 Item 1970 Item 1971 Item 1972 Item 1973 Item 1974 Item 1975 Item 1976 Item 1977 Item 1978 Item 1979 Item 1980 Item 1981 Item 1982 Item 1983 Item 1984 Item 1985 Item 1986 Item 1987 Item 1988 Item 1989 Item 1990 Item 1991 Item 1992 Item 1993 Item 1994 Item 1995 Item 1996 Item 1997 Item 1998 Item 1999 Item 2000 Item 2001 Item 2002 Item 2003 Item 2004 Item 2005 Item 2006 Item 2007 Item 2008 Item 2009 Item 2010 Item 2011 Item 2012 Item 2013 Item 2014 Item 2015 Item 2016 Item 2017 Item 2018 Item 2019 Item 2020 Item 2021 Item 2022 Item 2023 Item 2024 Item 2025 Item 2026 Item 2027 Item 2028 Item 2029 Item 2030 Item 2031 Item 2032 Item 2033 Item 2034 Item 2035 Item 2036 Item 2037 Item 2038 Item 2039 Item 2040 Item 2041 Item 2042 Item 2043 Item 2044 Item 2045 Item 2046 Item 2047 Item 2048 Item 2049 Item 2050 Item 2051 Item 2052 Item 2053 Item 2054 Item 2055 Item 2056 Item 2057 Item 2058 Item 2059 Item 2060 Item 2061 Item 2062 Item 2063 Item 2064 Item 2065 Item 2066 Item 2067 Item 2068 Item 2069 Item 2070 Item 2071 Item 2072 Item 2073 Item 2074 Item 2075 Item 2076 Item 2077 Item 2078 Item 2079 Item 2080 Item 2081 Item 2082 Item 2083 Item 2084 Item 2085 Item 2086 Item 2087 Item 2088 Item 2089 Item 2090 Item 2091 Item 2092 Item 2093 Item 2094 Item 2095 Item 2096 Item 2097 Item 2098 Item 2099 Item 2100 Item 2101 Item 2102 Item 2103 Item 2104 Item 2105 Item 2106 Item 2107 Item 2108 Item 2109 Item 2110 Item 2111 Item 2112 Item 2113 Item 2114 Item 2115 Item 2116 Item 2117 Item 2118 Item 2119 Item 2120 Item 2121 Item 2122 Item 2123 Item 2124 Item 2125 Item 2126 Item 2127 Item 2128 Item 2129 Item 2130 Item 2131 Item 2132 Item 2133 Item 2134 Item 2135 Item 2136 Item 2137 Item 2138 Item 2139 Item 2140 Item 2141 Item 2142 Item 2143 Item 2144 Item 2145 Item 2146 Item 2147 Item 2148 Item 2149 Item 2150 Item 2151 Item 2152 Item 2153 Item 2154 Item 2155 Item 2156 Item 2157 Item 2158 Item 2159 Item 2160 Item 2161 Item 2162 Item 2163 Item 2164 Item 2165 Item 2166 Item 2167 Item 2168 Item 2169 Item 2170 Item 2171 Item 2172 Item 2173 Item 2174 Item 2175 Item 2176 Item 2177 Item 2178 Item 2179 Item 2180 Item 2181 Item 2182 Item 2183 Item 2184 Item 2185 Item 2186 Item 2187 Item 2188 Item 2189 Item 2190 Item 2191 Item 2192 Item 2193 Item 2194 Item 2195 Item 2196 Item 2197 Item 2198 Item 2199 Item 2200 Item 2201 Item 2202 Item 2203 Item 2204 Item 2205 Item 2206 Item 2207 Item 2208 Item 2209 Item 2210 Item 2211 Item 2212 Item 2213 Item 2214 Item 2215 Item 2216 Item 2217 Item 2218 Item 2219 Item 2220 Item 2221 Item 2222 Item 2223 Item 2224 Item 2225 Item 2226 Item 2227 Item 2228 Item 2229 Item 2230 Item 2231 Item 2232 Item 2233 Item 2234 Item 2235 Item 2236 Item 2237 Item 2238 Item 2239 Item 2240 Item 2241 Item 2242 Item 2243 Item 2244 Item 2245 Item 2246 Item 2247 Item 2248 Item 2249 Item 2250 Item 2251 Item 2252 Item 2253 Item 2254 Item 2255 Item 2256 Item 2257 Item 2258 Item 2259 Item 2260 Item 2261 Item 2262 Item 2263 Item 2264 Item 2265 Item 2266 Item 2267 Item 2268 Item 2269 Item 2270 Item 2271 Item 2272 Item 2273 Item 2274 Item 2275 Item 2276 Item 2277 Item 2278 Item 2279 Item 2280 Item 2281 Item 2282 Item 2283 Item 2284 Item 2285 Item 2286 Item 2287 Item 2288 Item 2289 Item 2290 Item 2291 Item 2292 Item 2293 Item 2294 Item 2295 Item 2296 Item 2297 Item 2298 Item 2299 Item 2300 Item 2301 Item 2302 Item 2303 Item 2304 Item 2305 Item 2306 Item 2307 Item 2308 Item 2309 Item 2310 Item 2311 Item 2312 Item 2313 Item 2314 Item 2315 Item 2316 Item 2317 Item 2318 Item 2319 Item 2320 Item 2321 Item 2322 Item 2323 Item 2324 Item 2325 Item 2326 Item 2327 Item 2328 Item 2329 Item 2330 Item 2331 Item 2332 Item 2333 Item 2334 Item 2335 Item 2336 Item 2337 Item 2338 Item 2339 Item 2340 Item 2341 Item 2342 Item 2343 Item 2344 Item 2345 Item 2346 Item 2347 Item 2348 Item 2349 Item 2350 Item 2351 Item 2352 Item 2353 Item 2354 Item 2355 Item 2356 Item 2357 Item 2358 Item 2359 Item 2360 Item 2361 Item 2362 Item 2363 Item 2364 Item 2365 Item 2366 Item 2367 Item 2368 Item 2369 Item 2370 Item 2371 Item 2372 Item 2373 Item 2374 Item 2375 Item 2376 Item 2377 Item 2378 Item 2379 Item 2380 Item 2381 Item 2382 Item 2383 Item 2384 Item 2385 Item 2386 Item 2387 Item 2388 Item 2389 Item 2390 Item 2391 Item 2392 Item 2393 Item 2394 Item 2395 Item 2396 Item 2397 Item 2398 Item 2399 Item 2400 Item 2401 Item 2402 Item 2403 Item 2404 Item 2405 Item 2406 Item 2407 Item 2408 Item 2409 Item 2410 Item 2411 Item 2412 Item 2413 Item 2414 Item 2415 Item 2416 Item 2417 Item 2418 Item 2419 Item 2420 Item 2421 Item 2422 Item 2423 Item 2424 Item 2425 Item 2426 Item 2427 Item 2428 Item 2429 Item 2430 Item 2431 Item 2432 Item 2433 Item 2434 Item 2435 Item 2436 Item 2437 Item 2438 Item 2439 Item 2440 Item 2441 Item 2442 Item 2443 Item 2444 Item 2445 Item 2446 Item 2447 Item 2448 Item 2449 Item 2450 Item 2451 Item 2452 Item 2453 Item 2454 Item 2455 Item 2456 Item 2457 Item 2458 Item 2459 Item 2460 Item 2461 Item 2462 Item 2463 Item 2464 Item 2465 Item 2466 Item 2467 Item 2468 Item 2469 Item 2470 Item 2471 Item 2472 Item 2473 Item 2474 Item 2475 Item 2476 Item 2477 Item 2478 Item 2479 Item 2480 Item 2481 Item 2482 Item 2483 Item 2484 Item 2485 Item 2486 Item 2487 Item 2488 Item 2489 Item 2490 Item 2491 Item 2492 Item 2493 Item 2494 Item 2495 Item 2496 Item 2497 Item 2498 Item 2499 Item 2500 Item 2501 Item 2502 Item 2503 Item 2504 Item 2505 Item 2506 Item 2507 Item 2508 Item 2509 Item 2510 Item 2511 Item 2512 Item 2513 Item 2514 Item 2515 Item 2516 Item 2517 Item 2518 Item 2519 Item 2520 Item 2521 Item 2522 Item 2523 Item 2524 Item 2525 Item 2526 Item 2527 Item 2528 Item 2529 Item 2530 Item 2531 Item 2532 Item 2533 Item 2534 Item 2535 Item 2536 Item 2537 Item 2538 Item 2539 Item 2540 Item 2541 Item 2542 Item 2543 Item 2544 Item 2545 Item 2546 Item 2547 Item 2548 Item 2549 Item 2550 Item 2551 Item 2552 Item 2553 Item 2554 Item 2555 Item 2556 Item 2557 Item 2558 Item 2559 Item 2560 Item 2561 Item 2562 Item 2563 Item 2564 Item 2565 Item 2566 Item 2567 Item 2568 Item 2569 Item 2570 Item 2571 Item 2572 Item 2573 Item 2574 Item 2575 Item 2576 Item 2577 Item 2578 Item 2579 Item 2580 Item 2581 Item 2582 Item 2583 Item 2584 Item 2585 Item 2586 Item 2587 Item 2588 Item 2589 Item 2590 Item 2591 Item 2592 Item 2593 Item 2594 Item 2595 Item 2596 Item 2597 Item 2598 Item 2599 Item 2600 Item 2601 Item 2602 Item 2603 Item 2604 Item 2605 Item 2606 Item 2607 Item 2608 Item 2609 Item 2610 Item 2611 Item 2612 Item 2613 Item 2614 Item 2615 Item 2616 Item 2617 Item 2618 Item 2619 Item 2620 Item 2621 Item 2622 Item 2623 Item 2624 Item 2625 Item 2626 Item 2627 Item 2628 Item 2629 Item 2630 Item 2631 Item 2632 Item 2633 Item 2634 Item 2635 Item 2636 Item 2637 Item 2638 Item 2639 Item 2640 Item 2641 Item 2642 Item 2643 Item 2644 Item 2645 Item 2646 Item 2647 Item 2648 Item 2649 Item 2650 Item 2651 Item 2652 Item 2653 Item 2654 Item 2655 Item 2656 Item 2657 Item 2658 Item 2659 Item 2660 Item 2661 Item 2662 Item 2663 Item 2664 Item 2665 Item 2666 Item 2667 Item 2668 Item 2669 Item 2670 Item 2671 Item 2672 Item 2673 Item 2674 Item 2675 Item 2676 Item 2677 Item 2678 Item 2679 Item 2680 Item 2681 Item 2682 Item 2683 Item 2684 Item 2685 Item 2686 Item 2687 Item 2688 Item 2689 Item 2690 Item 2691 Item 2692 Item 2693 Item 2694 Item 2695 Item 2696 Item 2697 Item 2698 Item 2699 Item 2700 Item 2701 Item 2702 Item 2703 Item 2704 Item 2705 Item 2706 Item 2707 Item 2708 Item 2709 Item 2710 Item 2711 Item 2712 Item 2713 Item 2714 Item 2715 Item 2716 Item 2717 Item 2718 Item 2719 Item 2720 Item 2721 Item 2722 Item 2723 Item 2724 Item 2725 Item 2726 Item 2727 Item 2728 Item 2729 Item 2730 Item 2731 Item 2732 Item 2733 Item 2734 Item 2735 Item 2736 Item 2737 Item 2738 Item 2739 Item 2740 Item 2741 Item 2742 Item 2743 Item 2744 Item 2745 Item 2746 Item 2747 Item 2748 Item 2749 Item 2750 Item 2751 Item 2752 Item 2753 Item 2754 Item 2755 Item 2756 Item 2757 Item 2758 Item 2759 Item 2760 Item 2761 Item 2762 Item 2763 Item 2764 Item 2765 Item 2766 Item 2767 Item 2768 Item 2769 Item 2770 Item 2771 Item 2772 Item 2773 Item 2774 Item 2775 Item 2776 Item 2777 Item 2778 Item 2779 Item 2780 Item 2781 Item 2782 Item 2783 Item 2784 Item 2785 Item 2786 Item 2787 Item 2788 Item 2789 Item 2790 Item 2791 Item 2792 Item 2793 Item 2794 Item 2795 Item 2796 Item 2797 Item 2798 Item 2799 Item 2800 Item 2801 Item 2802 Item 2803 Item 2804 Item 2805 Item 2806 Item 2807 Item 2808 Item 2809 Item 2810 Item 2811 Item 2812 Item 2813 Item 2814 Item 2815 Item 2816 Item 2817 Item 2818 Item 2819 Item 2820 Item 2821 Item 2822 Item 2823 Item 2824 Item 2825 Item 2826 Item 2827 Item 2828 Item 2829 Item 2830 Item 2831 Item 2832 Item 2833 Item 2834 Item 2835 Item 2836 Item 2837 Item 2838 Item 2839 Item 2840 Item 2841 Item 2842 Item 2843 Item 2844 Item 2845 Item 2846 Item 2847 Item 2848 Item 2849 Item 2850 Item 2851 Item 2852 Item 2853 Item 2854 Item 2855 Item 2856 Item 2857 Item 2858 Item 2859 Item 2860 Item 2861 Item 2862 Item 2863 Item 2864 Item 2865 Item 2866 Item 2867 Item 2868 Item 2869 Item 2870 Item 2871 Item 2872 Item 2873 Item 2874 Item 2875 Item 2876 Item 2877 Item 2878 Item 2879 Item 2880 Item 2881 Item 2882 Item 2883 Item 2884 Item 2885 Item 2886 Item 2887 Item 2888 Item 2889 Item 2890 Item 2891 Item 2892 Item 2893 Item 2894 Item 2895 Item 2896 Item 2897 Item 2898 Item 2899 Item 2900 Item 2901 Item 2902 Item 2903 Item 2904 Item 2905 Item 2906 Item 2907 Item 2908 Item 2909 Item 2910 Item 2911 Item 2912 Item 2913 Item 2914 Item 2915 Item 2916 Item 2917 Item 2918 Item 2919 Item 2920 Item 2921 Item 2922 Item 2923 Item 2924 Item 2925 Item 2926 Item 2927 Item 2928 Item 2929 Item 2930 Item 2931 Item 2932 Item 2933	

DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



DATE: FILE:

TYPICAL LOCATION OF CROSSROAD SIGNS




1. The typical advance signing on a crossroad approach should be a "ROAD WORK AHEAD" (W20-10) sign and a "ROAD WORK" (W20-11) sign, unless noted otherwise in the plans.
2. The Engineer may use the reduced size 36" x 48" ROAD WORK AHEAD (W20-10) sign mounted back to back with the reduced size 36" x 48" ROAD WORK (W20-11) sign on low volume crossroads take note 4 under "GENERAL NOTES".
3. The Engineer may use the reduced size 36" x 48" ROAD WORK NEXT 1/2 MILE (W20-12) sign on low volume crossroads take note 4 under "GENERAL NOTES".
4. The Engineer will determine whether a road is low volume. This information should be shown in the plans.
5. Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLUORESCENT AHEAD, LODES CHARGE, or other appropriate signs. When additional signs are required, these signs will be shown in the plans.
6. The "ROAD WORK NEXT 1/2 MILE" (W20-12) sign shall be required of high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a road is high volume. This information should be shown in the plans.
7. When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.

WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS





T-INTERSECTION



1. The Engineer will determine the types and location of any additional traffic control devices, such as a flagger or accompanying signs, or other signs, that should be used when work is being performed on or near an intersection.
2. If construction closes the road of a T-intersection the Contractor shall place the "CONTRACTOR MAINT" (W20-61) sign behind the Type 3 barriers for the road closure (see BC110) also. The "ROAD WORK NEXT 1/2 MILE" (W20-12) sign shall be replaced by the "CONTRACTOR MAINT" (W20-61) sign in the plans.

CSJ LIMITS AT T-INTERSECTION

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS



NOTES

1. The Contractor shall determine the appropriate distance between the advance signing and the work area. This distance shall be based on the posted speed limit. This distance shall be replaced by the "X" and shall be provided to the nearest whole mile with the approval of the Engineer. No decimals shall be used.
2. The "BEGIN WORK ZONE" (W20-97) and "END WORK ZONE" (W20-231) signs shall be used as shown on the sample layout when construction is occurring in or leaving a port of traffic. They inform the motorist of the beginning and ending of the work zone. Traffic fines may double if workers are present.
3. Required CSJ Limit signing. See Note 10 on BC111. TRAFFIC CONTROL DEVICES shall be used to control traffic during construction projects.
4. Area for placement of "ROAD WORK AHEAD" (W20-10) sign and other signs or devices as called for on the traffic control plan.
5. Contractor will install a regulatory speed limit sign at the end of the work zone.

TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING

SIGN		SPACING	
Sign Number	Conventional Road	Expressway/Freeway	Posted Sign A Speed Spacing "X"
W20-1	48" x 48"	48" x 48"	100'
W20-2	48" x 48"	48" x 48"	100'
W20-3	48" x 48"	48" x 48"	100'
W20-4	48" x 48"	48" x 48"	100'
W20-5	48" x 48"	48" x 48"	100'
W20-6	48" x 48"	48" x 48"	100'
W20-7	48" x 48"	48" x 48"	100'
W20-8	48" x 48"	48" x 48"	100'
W20-9	48" x 48"	48" x 48"	100'
W20-10	48" x 48"	48" x 48"	100'
W20-11	48" x 48"	48" x 48"	100'
W20-12	48" x 48"	48" x 48"	100'
W20-13	48" x 48"	48" x 48"	100'
W20-14	48" x 48"	48" x 48"	100'
W20-15	48" x 48"	48" x 48"	100'
W20-16	48" x 48"	48" x 48"	100'
W20-17	48" x 48"	48" x 48"	100'
W20-18	48" x 48"	48" x 48"	100'
W20-19	48" x 48"	48" x 48"	100'
W20-20	48" x 48"	48" x 48"	100'
W20-21	48" x 48"	48" x 48"	100'
W20-22	48" x 48"	48" x 48"	100'
W20-23	48" x 48"	48" x 48"	100'
W20-24	48" x 48"	48" x 48"	100'
W20-25	48" x 48"	48" x 48"	100'
W20-26	48" x 48"	48" x 48"	100'
W20-27	48" x 48"	48" x 48"	100'
W20-28	48" x 48"	48" x 48"	100'
W20-29	48" x 48"	48" x 48"	100'
W20-30	48" x 48"	48" x 48"	100'
W20-31	48" x 48"	48" x 48"	100'
W20-32	48" x 48"	48" x 48"	100'
W20-33	48" x 48"	48" x 48"	100'
W20-34	48" x 48"	48" x 48"	100'
W20-35	48" x 48"	48" x 48"	100'
W20-36	48" x 48"	48" x 48"	100'
W20-37	48" x 48"	48" x 48"	100'
W20-38	48" x 48"	48" x 48"	100'
W20-39	48" x 48"	48" x 48"	100'
W20-40	48" x 48"	48" x 48"	100'
W20-41	48" x 48"	48" x 48"	100'
W20-42	48" x 48"	48" x 48"	100'
W20-43	48" x 48"	48" x 48"	100'
W20-44	48" x 48"	48" x 48"	100'
W20-45	48" x 48"	48" x 48"	100'
W20-46	48" x 48"	48" x 48"	100'
W20-47	48" x 48"	48" x 48"	100'
W20-48	48" x 48"	48" x 48"	100'
W20-49	48" x 48"	48" x 48"	100'
W20-50	48" x 48"	48" x 48"	100'
W20-51	48" x 48"	48" x 48"	100'
W20-52	48" x 48"	48" x 48"	100'
W20-53	48" x 48"	48" x 48"	100'
W20-54	48" x 48"	48" x 48"	100'
W20-55	48" x 48"	48" x 48"	100'
W20-56	48" x 48"	48" x 48"	100'
W20-57	48" x 48"	48" x 48"	100'
W20-58	48" x 48"	48" x 48"	100'
W20-59	48" x 48"	48" x 48"	100'
W20-60	48" x 48"	48" x 48"	100'
W20-61	48" x 48"	48" x 48"	100'
W20-62	48" x 48"	48" x 48"	100'
W20-63	48" x 48"	48" x 48"	100'
W20-64	48" x 48"	48" x 48"	100'
W20-65	48" x 48"	48" x 48"	100'
W20-66	48" x 48"	48" x 48"	100'
W20-67	48" x 48"	48" x 48"	100'
W20-68	48" x 48"	48" x 48"	100'
W20-69	48" x 48"	48" x 48"	100'
W20-70	48" x 48"	48" x 48"	100'
W20-71	48" x 48"	48" x 48"	100'
W20-72	48" x 48"	48" x 48"	100'
W20-73	48" x 48"	48" x 48"	100'
W20-74	48" x 48"	48" x 48"	100'
W20-75	48" x 48"	48" x 48"	100'
W20-76	48" x 48"	48" x 48"	100'
W20-77	48" x 48"	48" x 48"	100'
W20-78	48" x 48"	48" x 48"	100'
W20-79	48" x 48"	48" x 48"	100'
W20-80	48" x 48"	48" x 48"	100'

GENERAL NOTES

1. Special or large size signs may be used as necessary.
2. Distance between signs should be increased as required to more than 150 feet on more complex work.
3. Distance between signs should be increased as required to more than 1/2 mile on more complex work.
4. 36" x 48" ROAD WORK AHEAD (W20-10) signs may be used on low volume crossroads at the discretion of the Engineer. See Note 2 under "Typical Location of Crossroad Signs".
5. Only diamond shaped warning sign sizes are indicated.
6. See sign size listing in "TRAFFIC" Sign Appendix or the "Standard Highway Sign Design" for "TODAY" model for complete list of available sign design sizes.

LEGEND	
—	Type 3 Barricade
XXX	Channelizing Devices
X	Sign
See Typical Construction Signing sheet 1 of the TxDOT for sign spacing requirements.	

SHEET 2 OF 12

TEXAS
Department of Transportation

BARRICADE AND CONSTRUCTION PROJECT LIMIT

BC(2)-14

7-13

DATE:
FILE:

TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits should be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project.

Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.

GUIDANCE FOR USE:

LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- a) rough road or damaged pavement surface
- b) substantial alteration of roadway geometrics (diversions)
- c) construction detours
- d) grade
- e) width
- f) other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

SHORT TERM WORK ZONE SPEED LIMITS


This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorist only when work activity is present. When work activity is not present, signs shall be removed or covered.

(See Removing or Covering on BC(4)).

GENERAL NOTES

1. Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
2. Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
3. Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
4. Frequency of work zone speed limit signs should be 40 mph and greater 0.2 to 2 miles 35 mph and less 0.2 to 1 mile
5. Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
6. Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (W3-5) sign, WORK ZONE (W20-50P) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to item 502.
7. Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
8. Techniques that may help reduce traffic speeds include but are not limited to:
 - A. Low enforcement.
 - B. Flagger stationed next to sign.
 - C. Portable changeable message sign (PCMS).
 - D. Low-power (dome) radar transmitter.
 - E. Speed monitor trailers or signs.
9. Speed signs on detours shall be for illustration only.
10. For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.




BARICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT		BC(3) - 14	
FILED 12/01/2002 9-07 8-14 7-13	DATE: 12/01/2002 TIME: 9-07 BY: 8-14 7-13	12/01/2002 9-07 8-14 7-13	12/01/2002 9-07 8-14 7-13

SHEET 3 OF 12

Texas Department of Transportation
Traffic Division
Standard


DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TYPICAL MINIMUM CLEARANCES FOR LONG TERM AND INTERMEDIATE TERM SIGNS




Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.

ATTACHMENT FOR SIGN SUPPORTS




Attachment to wooden supports will be by bolts and nuts or screws. Use TxDOT's or manufacturer's recommended procedures for attaching sign substrates to other types of sign supports



Each sign shall be attached directly to the sign support. Multiple signs shall not be joined or spliced by any means. Wood supports shall not be extended or repaired by splicing or other means.

STOP/SLOW PADDLES

1. STOP/SLOW paddle or the plicancy method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24" as detailed below.
2. When used at night, the STOP/SLOW paddle shall be retroreflective.
3. STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the STOP/SLOW paddle faces.
4. Any lights incorporated into the STOP/SLOW paddle faces shall only be as specifically detailed in Section 6E.03 Hand Signaling Devices in the MUTCD.



CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

1. Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, or convey information about the location of hazards, such as the location of sources of interest, and other geographical, recreational, or cultural information. Drivers proceeding through a work zone need the same, if not better, route guidance as normally travelled on a roadway without construction.
2. When permanent regulatory or warning signs conflict with work zone conditions, then permanent signs should be removed and the permanent sign message moves the roadway condition.
3. When existing permanent signs are moved and relocated due to construction purposes, they should be visible to motorists at all times.
4. If existing signs are to be relocated on their original substrate, they shall be replaced with new signs that meet the required mounting height shown on the BC Sheets or the S&D Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
5. If permanent signs are to be removed and relocated using temporary supports, the contractor shall use the appropriate sign support or the C&D. The signs shall meet the required mounting height shown on the BC Sheets or the S&D Standards during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
6. If the contractor is required to remove and relocate signs, the contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to item 502.

GENERAL NOTES FOR WORK ZONE SIGNS

1. Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
 2. When a sign post shall be painted with:
 3. All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
 4. The Contractor may furnish either the sign design shown in the plans or the "Standard Highway Sign Designs for Texas" (SHSD). The Contractor may, however, furnish the Contractor's own sign designs that are shown in the MCDOT but may have been omitted from the SHSD.
 5. Engineering the Contractor may, however, furnish the Contractor's own sign designs that are shown in the MCDOT but may have been omitted from the SHSD. All changes shall be documented in writing before being implemented. This can include documenting the changes in the Inspector's I-1007 diary and having both the Inspector and Contractor Initial and date the agreed upon changes.
 6. The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CZC2103). The Contractor shall furnish the sign supports and signposts that are required for the work zone. The Contractor shall furnish the sign supports and signposts that are required for the work zone. The Contractor shall furnish the sign supports and signposts that are required for the work zone.
 7. The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or verify the correct procedure and being fully loaded.
 8. The Contractor shall be responsible for selecting as directed by the Engineer/Inspector.
 9. Identification shall be made by the Contractor on the back of the sign substrates. The minimum height of letters and/or company logos used for identification shall be 1 inch.
 10. The Contractor shall replace damaged road posts. New or damaged road sign posts shall be applied.
- REVISION OF WORK ARE OBTAINED BY THE "Texas Manual on Uniform Traffic Control Devices" Part 6.1**
1. The type of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work zone. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crush/strength and duration of work requirements.
 2. Long-term stationary - work that occupies a location more than 3 days.
 3. Intermediate-term stationary - work that occupies a location more than one day/two night period up to 3 days, or nighttime work lasting 3 days.
 4. Short-term stationary - daytime work that occupies a location for more than 1 hour in a single day/two night period.
 5. Short, duration - work that occupies a location up to 1 hour.
 6. Mobile - work that moves continuously or intermittently (stop/stop for up to approximately 15 minutes.)

1. The bottom of Long-t

1. as seen for additional plumes mounted below other signs;
 2. the bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the pavement surface;
 3. Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signs;
 4. Short-term/Short Duration signs shall be used only during daylight and the end of the workday or rolled to support the Long-term/Intermediate term sign;
 5. Portable signs shall be mounted on trip legs, but not more than 9 feet, above the paved surface regardless of work duration.
- 4.2.2.2. SIGN CONTOUR**
- The Contractor shall furnish the sign signs shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.
- 4.2.2.3. SIGN MATERIALS**

1. The Contractor

1. Support "thru" the bearing zone. The CARTRIDGERS shown underneath them can be used on the different types and models of sign supports.
2. When "thru" material is not an approved sign substrate, regardless of the thickness of the window.
3. All wooden individual sign panels (cardstock, fiber or a near plastic shell) have one or more plastic clear 1/2" thick by 6" wide, 1/2" deep rectangular openings cut into the sign. When the sign is placed on the back of the sign using the CARTRIDGERS, the sign will be placed on the back of the sign.
4. When the sign is placed on the back of the sign, the sign will be placed on the back of the sign and spaced of 8 inches.
5. The Engineer may approve other methods of splicing the sign face.

1. All signs shall be

1. All SIGS letters and numbers should be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as outlined in the "Standard Highway Sign Design for Trucks, Buses, and Motorcycles" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.
2. All SIGS letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as outlined in the "Standard Highway Sign Design for Trucks, Buses, and Motorcycles" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.
3. Orange background, meeting the requirements of M-3200 Type B₁ or Type C₁, shall be used for rigid signs with orange backgrounds.

REMOVING OR COVERING

1. Long-term storability or "intermediate storability" signs installed on square metal tubing may be turned away from traffic 90 degrees.
2. The sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near or adjacent to a highway.
3. If the sign may be seen from opposing traffic, the sign may not be turned 90 degrees away from the roadway. These signs should be removed or completely covered when not required.
4. When signs are covered, the material used shall be opaque, such as heavy all black plastic, or other material which will cover the sign and not reflect light.
5. During snow or other weather conditions, signs should be removed or covered with opaque material.
6. Barbed wire or other obnoxious material shall not be affixed to a sign face.
7. Signs and other studs shall be removed and holes bottled up on completion of work.


SIGN SUPPORT WEIGHTS

1. The use of sandbags with dry, cohesionless sand should be used.
2. The sandbags will be tied shut to keep the sand from spilling and to prevent the sand from blowing away.
3. Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
4. Sandbags should be made of a durable material that weighs upon vehicle impact a minimum of 35 lbs and of a maximum of 50 lbs.
5. Sandbags should be placed on the ground.
6. Rubber bollards designed for communicating with vehicles should not be used for bollard on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CADDIS list.
7. Traffic control devices and shall not be suspended above ground level or attached to any structure. They shall be placed on a sign support and be placed along the length of the slide to weigh down the sign support.
8. Sandbags shall NOT be placed under the slide and shall not be used to leave sign supports placed on slopes.

PLACES ON SIGNS


- shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

DATE: _____
FILE: _____




SKID MOUNTED WOOD SIGN SUPPORTS

LONG/INTERMEDIATE TERM STATIONARY - PORTABLE SKID MOUNTED SIGN SUPPORTS ☐



SKID MOUNTED PERFORATED SQUARE STEEL TUBING SIGN SUPPORTS



GROUND MOUNTED SIGN SUPPORTS

Refer to the LNZTD and the manufacturer's installation procedure for each type sign support. The maximum sign square footage shall adhere to the manufacturer's recommendation. Two post installations can be used for larger signs.

WEDGE ANCHORS

Both steel and plastic Road Anchor Systems are shown on the S&D Standard Sheets may be used as temporary sign supports for signs up to 10 square feet of sign face. They may be set in concrete or in sturdy soil if approved by the Engineer. (See web address for "Traffic Engineering Standard Sheets" on BC(11)).

OTHER DESIGNS


MORE DETAILS OF APPROVED LONG/INTERMEDIATE AND SHORT TERM SUPPORTS CAN BE FOUND ON THE CMZTCD LIST. SEE BC(1) FOR WEBSITE LOCATION

GENERAL NOTES

2. No more than 2 sign posts shall be placed within 5 ft. of a sign, except for specific materials noted on the METHOD label.
3. When project is completed, all sign supports and foundations shall be removed from the project site. This will be considered satisfactory to Item 502.

North East Size	Number of Pours	Maximum Sq. feet of Sign Face	Maximum Soil Embedment	Brilliant Holographic Refracted
4 X 4	1	12	36"	NO
4 X 4	2	21	36"	NO
4 X 4	1	21	36"	YES
4 X 6	2	36	36"	YES

**MOOD POST SYSTEM FOR GROUND
MOUNTED SIGN SUPPORTS**



BARRICADE AND CONSTRUCTION TYPICAL SIGN SUPPORT

SHEET 5 OF 12



Department of Transportation	Traffic Operations Division Standard
------------------------------	--------------------------------------

BC(5) - 14

[illegible]

DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

1. The Engineer/inspector shall approve all messages used on portable electronic message alarm panels.
2. Messages shall be limited to no more than 8 words (about 160 characters) per word, not including simple words such as "To," "From," "At," etc.
3. Messages should consist of a single phrase, or two phrases that otherwise, three-phrase messages are not allowed, each phrase of the message should convey a single thought, and must be understood by 100% of the intended audience.
4. Use the word "EXIT" to refer to an exit ramp on a freeway 1, e.g., "EXIT CLOSED. Do not use the term 'Ramp'."
5. Always use the route or Interstate designation (114, 55, 54, 780).
6. When in use, the bottom of the roadway PMS message panel should be a minimum 1' feet above the shoulder, where possible.
7. The message term "RECEIVED" should be used only if the work is to be received by a specific person or unit, such as the PMS Unit.
8. The Engineer/inspector may select one of two options which are available for displaying a two-phrase message on a PMS. Each phrase may be no more than 8 words, and must be understood by 100% of the intended audience.
9. Do not "fill" messages or words included in a message. The message should be steady burn or continuous while a message is displayed.
10. Do not present redundant information on a two-phrase message 1, e.g., "Missing two lanes of the message 'LANE SHIFT LEFT' or 'LANE SHIFT RIGHT'."
11. Do not display the message "LANE SHIFT LEFT" or "LANE SHIFT RIGHT" on a PMS. Drivers do not understand the message.
12. Do not display messages that scroll non-horizontally or vertically across the face of the sign.
13. The message shall consist of abbreviations and two-word phrases that are acceptable for use on a PMS. Both words in a phrase shall be displayed together, word or phrase not on this list should not be displayed, unless shown in the MUTCD.
14. The message shall be displayed in the following manner:
a. For a single phrase message, the message shall be displayed in a single line of text, should be legible from at least 1/2 mile or less 1/2 mile and the text should be the legible from at least 600 feet or night and 800 feet in daylight. Text marked units must have a character height of 10 inches or greater.
15. For a two-phrase message, the message shall be displayed in two lines of text, should be legible from at least 1/2 mile or less 1/2 mile and the text should be the legible from at least 600 feet or night and 800 feet in daylight. Text marked units must have a character height of 10 inches or greater.
16. If displayed, the PMS should default to a 114 legible display, that will have no information, a pattern such as a series of horizontal solid bars is appropriate.

[illegible]

(The Engineer may approve other messages not specifically covered here.

Phase 2: Possible Component Lists

Other Condition List

FREEWAY CLOSED X MILE	ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT	FLAGGER XXXX FT	ROAD LANE NARROWS XXXX FT
ROAD CLOSED AT PM XXXX	RIGHT LN CLOSED XXX FT	RIGHT LN CLOSED XXXX FT	RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
RIGHT X LANES CLOSED	RIGHT X LANES OPEN	MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT	
CENTER LANE CLOSED	DAYTIME LANE CLOSED	LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT	
NIGHT LANE CLOSURES	1-XX SOUTH EXIT CLOSED	DETOUR X MILE	ROUGH ROAD XXXX FT	
VARIOUS LANES CLOSED	EXIT XXX CLOSED X MILE	ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN	
EXIT CLOSED	RIGHT LN CLOSED	BUMP XXXX FT	US XXX EXIT X MILES	
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI	TRAFFIC SIGNAL XXXX FT	LANES SHIFT	
XXXXXXX BLVD CLOSED				

* LANE(S) SHIFT IN Phase 1 must be used with STAY IN LANE. IN Phase 2.

Occupation

Phase 2: Possible Component Lists

MERGE RIGHT	FORM X LINES RIGHT	AT FM XXXX	SPEED LIMIT XX MPH	TUE-FRI XX AM- X PM
DETOUR NEXT X EXITS	USE XXXXX RD EXIT	BEFORE RAILROAD CROSSING	MAXIMUM SPEED XX MPH	APR XX- X PM-X AM
USE EXIT XXX	USE EXIT 1-XX NORTH	NEXT MILES	MINIMUM SPEED XX MPH	BEGINS MONDAY
STAY ON US XXX SOUTH	USE 1-XX E TO 1-XX N	PAST US XXX EXIT	ADVISORY SPEED XX MPH	BEGINS MAY XX
TRUCKS USE US XXX N	WATCH FOR TRUCKS	XXXXXXX TO XXXXXXX	RIGHT LANE EXIT	MAY X-X XX PM - XX AM
WATCH FOR TRUCKS	EXPECT DELAYS	US XXX XXXXXX	USE CAUTION	NEXT FRI-SUN
EXPECT DELAYS	PREPARE TO STOP		DRIVE SAFELY	XX AM TO XX PM
REDUCE SPEED XX FT	END SHOULDER USE		DRIVE WITH CARE	NEXT AUG XX
USE OTHER ROUTES	WATCH FOR WORKERS			TONIGHT XX PM- XX AM
STAY IN LANE				

* See Application Guidelines more 6.

1. Only 1 or 2 phases are to be used on a PCMS.

1. The 1st phase (or 1st) should be selected from the "Headlines/Phase Clause List" and the "Other Condition List".
2. The 2nd phase should be selected from the Action to be performed, the Action to be avoided, the Action to be performed, General Identity, or Address (not a phase list).
3. The 3rd phase is necessary only if a distance or location is not included in the 1st phase selected.
4. If two PDS are included in sequence, they may be separated by a minimum of 1000 ft. Each PDS should be limited to two phases.
5. For the advance notice, when the current dose is replaced with a new dose, the advance notice should typically be for no more than one week or up to the work.

1. The words RIGHT, LEFT and ALL can be interchanged as appropriate.


2. Redundancy designations *IR*, *US*, *SH*, *FM* and *LP* can be interchanged as appropriate.
3. *EAST*, *WEST*, *NORTH* and *SOUTH* for observations *E*, *W*, *N* and *S* can be interchanged as appropriate.
4. *REAR*, *HEAD*, *RIGHT* and *LEFT* can be interchanged as appropriate.
5. *ROAD*, *HIGHWAY* and *FREEWAY* can be interchanged as needed.
6. *AHEAD* may be used instead of distances if necessary.
7. *FT* and *MI*, and *MILES* interchanged as appropriate.
8. *AT*, *BEFORE* and *PAST* interchanged as needed.
9. Distances or *AHEAD* can be eliminated from the message if location phrase is used.

POMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE POMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

1. When Full Matrix POMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE".


- CHANGING MESSAGE SLOTS' above.
- The new symbol signs, such as the "Frogger Symbol" ("CICR-0") are represented graphically on the Full Matrix PDS sign and, with the approval of the Engineer, it may be used by the Contractor to indicate the location of the Full Matrix PDS sign. When approved, the Contractor shall submit a copy of the sign design to the Engineer for review and approval.
- When approval is given or requested graphically on the Full Matrix PDS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace their sign.
- A full matrix PDS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BCTI, for the same size sign.

DATE:
FILE#



CONCRETE TRAFFIC BARRIER (CTB)

- [illegible]




LOW PROFILE CONCRETE BARRIER (LPCB)

DELINEATION OF END TREATMENTS

**END TREATMENTS FOR
CTB'S USED
IN WORK ZONES**

BARRIER REFLECTORS FOR CONCRETE TRAFFIC BARRIER AND ATTENUATORS



WARNING LIGHTS


1. Warning lights shall meet the requirements of the TATD.
2. Warning lights shall NOT be installed on front fenders. They are intended to warn or mark a potentially hazardous area. Their use should be indicated on the sheet covering other details of the designator "FL". The Type A warning lights also may be used on trucks manufactured with type B₀ or B₁ steering meeting the requirements of Department DMV-6350.
3. Type-C and Type D 360 degree Steady Burn Lights are intended to be used in a series for delineation to augment other traffic control devices. This use will not be indicated on the sheet covering other details of the plan by the designator "SS".
4. Type E and Type F 360 degree Steady Burn Lights are intended to be used as a means of traffic control devices.
5. When installed by the Engineer, the Contractor shall furnish a copy of the warning lights certification. The warning light manufacturer will certify the warning lights meet the requirements of the latest ITE Purposes Specifications for Flushing and Steady-Burn Warning Lights.
6. When used to delineate curves, Type-C and Type D Steady Burn Lights should only be placed on the outside of the curve, not the inside.
7. The location of warning lights on warning reflections on drums shall be as shown elsewhere in the plans.

WARNING LIGHTS MOUNTED ON PLASTIC DRUMS

1. Type A flashing warning lights are intended to warn of a hazard that they are approaching, or are in a potentially hazardous area.
2. Type B flashing warning lights are not intended for use in the rear of a vehicle, but may be used for attention. If used in the rear of a vehicle, they should be used in conjunction with a stop lamp.
3. The sequential flashing of the sequential warning lights should occur from the beginning of the stop, to the end of the merging flow. In order to identify the desired vehicle position, the rate of flashing for each light shall be 65 flashes per minute, plus or minus 10 flashes.
4. Type C and D steady-state warning lights are intended to be used in a series to delineate the edge of the travel lane on curves, on cross streets, and on narrow lanes.
5. Type C and D steady-state warning lights shall be installed at locations as detailed on other sheets in the plans.
6. Warning lights shall not be installed on a dual road with a sign, chevron or vertical panel.
7. The maximum spacing for warning lights on dual roads should be identical to the maximum device spacing.

WARNING REFLECTORS MOUNTED ON PLASTIC DRUMS AS A SUBSTITUTE FOR TYPE C (STEADY BURN) WARNING LIGHTS

1. A warning reflector approved under this note may be mounted on a plastic drum as a substitute for a Type A, energy lamp warning light for the distribution of the Contractor unless otherwise noted in the Plans.
2. The warning reflector shall be yellow in color and shall be manufactured using a glass substrate approved for use with plastic drums listed on the ODOT.
3. The warning reflector shall have a minimum reflective surface and top-sidel of 30 square inches.
4. Round reflective shall be fully reflective, 20. Including the rear, when attached to the drum.
5. The warning reflector shall be a minimum of 30 degree flares of reflective sheeting. They do not have to be reflective 200 where it attaches to the drum.
6. The side of the warning reflector facing approaching traffic shall have meeting meeting the color and reflectivity requirements for reflective sheeting.
7. The warning reflector, both sides of the warning reflector shall be reflective.
8. The warning reflector should be mounted on the side of the metal nearest approaching traffic.
9. The warning reflector should be designed to be designed to the mounting device spacing requirements.



Morning reflector may be round or square. Must have a yellow reflective surface area of at least 30 square inches

FLASHING ARROW BOARDS


REQUIREMENTS			
TYPE	MINIMUM SIZE	MINIMUM NUMBER OF PANEL LAMPS	MINIMUM VISIBILITY DISTANCE
B	30 x 60	13	3/4 mile
C	48 x 96	15	1 mile

ATTENTION

shall be equipped with automatic dimming devices.

6.

WHEN NOT IN USE, REMOVE THE ARROW BOARD FROM THE RIGHT-OF-WAY OR PLACE THE ARROW BOARD BEHIND CONCRETE TRAFFIC BARRIER OR GUARDRAIL.



- Arrow Boards may be located behind channelizing devices in place for a shoulder taper or merging taper, otherwise they shall be delineated with four (4) channelizing devices placed perpendicular to traffic on the upstream side of traffic.
1. The Flashing Arrow Board should be used for all lane closures on multi-lane roadways, or slow moving maintenance or construction activities on the travel lanes.
 2. Flashing Arrow Boards should not be used on two-lane, two-way roadways, detours, diversions or temporary detours.
 3. The Engineer/Inspector will choose all appropriate signs, barricades and/or other traffic control devices that should be used in conjunction with the Flashing Arrow Board.
 4. The Flashing Arrow Board should be able to display the following symbols:
- | | | | |
|------------------|-----------------------------|--|--|
|
DOUBLE ARROW | OR
 | | |
| | ALTERNATING DIAMOND CAUTION | | |
5. The "CAUTION" display consists of four corner shape flashing simultaneously, or the Alternating diamond caution mode as shown.
 6. The Flashing Arrow Board display is NOT ALLOWED.
 7. The Flashing Arrow Board shall be capable of minimum 90 percent dimming from rated lamp voltage.
 8. The flashing rate of the lamps shall not be less than 25 nor more than 40 flashes per minute.
 9. Minimum ramp up time shall be approximately 50 percent for the flashing arrow and equal to the sequential arrow display is NOT ALLOWED.
 10. The flashing arrow display is the INDOT standard; however, the sequential Chevron display may be used during day light operations.
 11. The Flashing Arrow Board shall have a minimum one-half mile, trailer or other suitable support.
 12. A full inertia pole shall not be used to simulate a Flashing Arrow Board provided it meets visibility.
 13. A Flashing Arrow Board shall NOT be used to laterally shift traffic.
 14. When used at night, the Flashing Arrow Board shall be fully illuminated from roadway to bottom of panel.

SHEET 7 OF 12

**BARRICADE AND CONSTRUCTION
ARROW PANEL, REFLECTORS,
WARNING LIGHTS & ATTENUATOR**

BC(7)-14

POLICE	DO-14, QRTT	PER TROOP	CAS TROOP	PER TROOP	CAS TROOP
7-07 9-13	8-14	NOVEMBER 2002	CONTRACT	ADJ	ALLEGAT
NOTATIONS					
	0912	M4	143	C5	
	0188	COUNTY		SHEET NO.	
HQ	FORT BEN		25		

DATE:
FILE:



1. For long term stationary work zones on freeways, drums shall be used as the primary stationing device.
2. For intermediate term stationary work zones on freeways, drums shall be used as the primary stationing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, two-piece cones may be used in the approach of one station but only if the drums are placed at 601' intervals to maintain the line.
3. For short term stationary work zones on freeways, drums are the preferred stationing device but may be replaced in tangent, transitional and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
4. Drums and all related items shall comply with the requirements of the current version of the Texas Manual on Uniform Traffic Control Devices (TMUTCD) and the Comptroller Work Zone Traffic Control Devices List (CWTCDL).
5. Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or use.
6. The Contractor shall have a minimum of 24 hours to replace any stationing device identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

[illegible]



1. Unload crates, boxes and bags, except to hold up to 50 lbs. of rice.
2. Use bins, when filled with the bolsters stacked, should stack between 35 lbs minimum and 50 lbs maximum. The bolsters may be sent in one to three sandbags separate from the bins, and in a sack-filled plastic bag, or other bolting device, as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
3. Bolsters with ball-in-bolts shall weigh between 40 lbs. and 50 lbs.
4. Bolsters shall be constructed of an integral crane rubber base or a solid rubber base.
5. Replaced truck tire sidewall is to be used for bolsters on cranes approved for this type of bolsters on the CRD101101.
6. The bolsters shall not be heavy objects, metal, or any material that would become hazardous to motorists, pedestrians, or vehicles when the bolsters are used.
7. Bolsters are not responsible for freezing, cranes shall have crimping holes in the bottom so that water will not collect and freeze becoming a hazard when struck by a vehicle.
8. Bolsters shall not be placed on top of cranes.
9. Bolsters shall not be placed on top of drums.
10. Bolsters may not be placed on top of drums to government.

1. The Direction Indicator (Barricade) may be used in traffic, construction, and other areas where specific directional control is required.
2. If used, the Direction Indicator Barricade should be used in series to direct the driver through this transition and into the correct lane.
3. The Direction Indicator Barricade shall consist of one Directional Arrow (DAI-6) sign in the left lane with a black arrow pointing left and one in the right lane with a black arrow pointing right. The signs shall be placed on the leading edge of the white and orange striped sloping downward of an end of a road or on the shoulder of a road.
4. The Direction Indicator Barricade shall be placed on the road ends of a loop, weaving loop or a loop and exit ramp.
5. Double arrows on the Direction Indicator Barricade will not be used.
6. All manufacturers are shown on the ODOT List.

Barricade must be as approved by the manufacturers' instructions.


[illegible]

Plywood, Aluminum or Metal sign substrates shall NOT be used on plastic drums




18" x 24" Sign Maximum Sign Dimensions Chevron CBI-8, Opposing Traffic Lane Dividers, Derivative sign 0100, Keep Right R4 series or other signs as approved by Engineer	12" x 24" Vertical Panel mount with diagonal slating down forward travel way
--	--

BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

 Texas Department of Transportation	Traffic Operations Standard
	BC(8) - 14
BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES	
ITEM: BC-14-000 QTY: 2000 REVISIONS: 4-03 7-13 9-07 BC-14	REV: 1000 REV: 1001 REV: 1002 REV: 1003 REV: 1004 REV: 1005 REV: 1006 REV: 1007 REV: 1008 REV: 1009 REV: 1010 REV: 1011 REV: 1012 REV: 1013 REV: 1014 REV: 1015 REV: 1016 REV: 1017 REV: 1018 REV: 1019 REV: 1020 REV: 1021 REV: 1022 REV: 1023 REV: 1024 REV: 1025 REV: 1026 REV: 1027 REV: 1028 REV: 1029 REV: 1030 REV: 1031 REV: 1032 REV: 1033 REV: 1034 REV: 1035 REV: 1036 REV: 1037 REV: 1038 REV: 1039 REV: 1040 REV: 1041 REV: 1042 REV: 1043 REV: 1044 REV: 1045 REV: 1046 REV: 1047 REV: 1048 REV: 1049 REV: 1050 REV: 1051 REV: 1052 REV: 1053 REV: 1054 REV: 1055 REV: 1056 REV: 1057 REV: 1058 REV: 1059 REV: 1060 REV: 1061 REV: 1062 REV: 1063 REV: 1064 REV: 1065 REV: 1066 REV: 1067 REV: 1068 REV: 1069 REV: 1070 REV: 1071 REV: 1072 REV: 1073 REV: 1074 REV: 1075 REV: 1076 REV: 1077 REV: 1078 REV: 1079 REV: 1080 REV: 1081 REV: 1082 REV: 1083 REV: 1084 REV: 1085 REV: 1086 REV: 1087 REV: 1088 REV: 1089 REV: 1090 REV: 1091 REV: 1092 REV: 1093 REV: 1094 REV: 1095 REV: 1096 REV: 1097 REV: 1098 REV: 1099 REV: 1100 REV: 1101 REV: 1102 REV: 1103 REV: 1104 REV: 1105 REV: 1106 REV: 1107 REV: 1108 REV: 1109 REV: 1110 REV: 1111 REV: 1112 REV: 1113 REV: 1114 REV: 1115 REV: 1116 REV: 1117 REV: 1118 REV: 1119 REV: 1120 REV: 1121 REV: 1122 REV: 1123 REV: 1124 REV: 1125 REV: 1126 REV: 1127 REV: 1128 REV: 1129 REV: 1130 REV: 1131 REV: 1132 REV: 1133 REV: 1134 REV: 1135 REV: 1136 REV: 1137 REV: 1138 REV: 1139 REV: 1140 REV: 1141 REV: 1142 REV: 1143 REV: 1144 REV: 1145 REV: 1146 REV: 1147 REV: 1148 REV: 1149 REV: 1150 REV: 1151 REV: 1152 REV: 1153 REV: 1154 REV: 1155 REV: 1156 REV: 1157 REV: 1158 REV: 1159 REV: 1160 REV: 1161 REV: 1162 REV: 1163 REV: 1164 REV: 1165 REV: 1166 REV: 1167 REV: 1168 REV: 1169 REV: 1170 REV: 1171 REV: 1172 REV: 1173 REV: 1174 REV: 1175 REV: 1176 REV: 1177 REV: 1178 REV: 1179 REV: 1180 REV: 1181 REV: 1182 REV: 1183 REV: 1184 REV: 1185 REV: 1186 REV: 1187 REV: 1188 REV: 1189 REV: 1190 REV: 1191 REV: 1192 REV: 1193 REV: 1194 REV: 1195 REV: 1196 REV: 1197 REV: 1198 REV: 1199 REV: 1200 REV: 1201 REV: 1202 REV: 1203 REV: 1204 REV: 1205 REV: 1206 REV: 1207 REV: 1208 REV: 1209 REV: 1210 REV: 1211 REV: 1212 REV: 1213 REV: 1214 REV: 1215 REV: 1216 REV: 1217 REV: 1218 REV: 1219 REV: 1220 REV: 1221 REV: 1222 REV: 1223 REV: 1224 REV: 1225 REV: 1226 REV: 1227 REV: 1228 REV: 1229 REV: 1230 REV: 1231 REV: 1232 REV: 1233 REV: 1234 REV: 1235 REV: 1236 REV: 1237 REV: 1238 REV: 1239 REV: 1240 REV: 1241 REV: 1242 REV: 1243 REV: 1244 REV: 1245 REV: 1246 REV: 1247 REV: 1248 REV: 1249 REV: 1250 REV: 1251 REV: 1252 REV: 1253 REV: 1254 REV: 1255 REV: 1256 REV: 1257 REV: 1258 REV: 1259 REV: 1260 REV: 1261 REV: 1262 REV: 1263 REV: 1264 REV: 1265 REV: 1266 REV: 1267 REV: 1268 REV: 1269 REV: 1270 REV: 1271 REV: 1272 REV: 1273 REV: 1274 REV: 1275 REV


DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:



FIXED
(Rigid or self-righting)


DRIVEABLE



1. The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
2. Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for horizontal alignment of the roadway.
3. Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the driver's change in alignment eliminates its need.
4. To be effective, the chevron should be visible for at least 500 feet.
5. Chevrons shall be erected with a black reflective legend. Spacing for the chevron shall be determined by the Engineer/Inspector and shall conform to Department Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
6. For long term storage use on topography or other conditions where the use of a single self-righting chevron may be used to replace plastic drums but not to replace plastic drums.

CHEVRONS


- GENERAL NOTES**
1. Work zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roads and in accordance with the Texas Manual on Uniform Traffic Control Devices (TMUTCD).
 2. Channelizing devices shown on this sheet may have a fixed or portable base. The requirement for channelizing devices must be specified in the General Notes or other plan sheets.
 3. Channelizing devices are frequently required to maintain vehicles or vehicle related items making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be established where in the plan. These devices shall conform to the TMUTCD and the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
 4. The Engineer/Inspector shall be required to maintain proper device spacing and alignment.
 5. Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs. that ensures proper bonding between the device and the pavement surface.
 6. Portable bases shall be prepared and applied according to the manufacturer's recommendation.
 7. The installation and removal of channelizing devices shall not cause damage to the road surface or the pavement surface. The Contractor shall be permitted to finish pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.



1. Vertical Panels (VPs) are normally used to channelize traffic or divide opposing lanes of traffic.
2. They may be used on the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the roadway design and construction specifications for additional guidelines on the use of VPs for drop-offs.
3. VPs should be mounted back to back if used at the edge of cuts or embankments to two-way roadways. VPs should be mounted back to back if used at the edge of cuts or embankments to one-way roadways. VPs should be used on expressways and freeways or other high speed roadways, may have more than 210 square inches of reflective area facing traffic.
4. Self-righting devices shall be used in portable bases. See Compliant Work Zone Traffic Control Devices List* (CWTCD).
5. Spacing for the VPs shall be retroreflective Type A unless noted otherwise.
6. Where the height of reflective material on the vertical panel is 36 inches or greater, a panel width of 6 inches shall be used.


PORTABLE

VERTICAL PANELS (VPs)



1. Opposing Traffic Lane Dividers (OTLDs) are delineation devices designed to convert a narrow one-way roadway section to two-way operation. OTLDs are used on temporary construction projects and on permanent projects where the direction of traffic on either side of the divider. The divider is secured to the pavement with an adhesive or rubber weight to inhibit movement caused by a vehicle impact or wind gust.
2. The OTLD may be used in combination with 42" cones or VPs.
3. Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLDs should not exceed 100 foot spacing.
4. The OTLD shall be orange with a black non-reflective legend. Spacing for the OTLD shall be retroreflective Type B₂ or Type C₂ conforming to Department Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.

OPPOSING TRAFFIC LANE DIVIDERS (OTLD)



- LONGITUDINAL CHANNELIZING DEVICES (LCDs)**
1. LCDs are temporary, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on a highway.
 2. LCDs may be placed in accordance to application and installation requirements specific to the device, and shall be placed in accordance to application and installation requirements specific to the device.
 3. LCDs shall be placed in accordance to application and installation requirements specific to the device, and shall be placed in accordance to application and installation requirements specific to the device.
 4. LCDs shall not be used to provide positive protection for obstacles, pedestrians or workers.
 5. LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(1) when placed roughly parallel to the travel lanes.
 6. LCDs used as barriers placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for portable rolls as shown on BC(10) placed near the top of the LCD along the full length of the device.

WATER BALLASTED SYSTEMS USED AS BARRIERS

1. Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate MCDP 350 guidelines. Requirements based on roadway speed and barrier application.
2. Water ballasted systems used to channelize traffic shall be supplemented with retroreflective delineation.
3. Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWTCD list.
4. Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 mph) areas. Water ballasted systems used as barriers should be tapered to the taper length.
5. When water ballasted systems used as barriers show blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or fixed to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems shall be placed in accordance with the requirements of the Texas Manual on Uniform Traffic Control Devices (TMUTCD) and shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

Rated Speed	Formula	Minimum Taper Length	Suggested Maximum Channelizing Spacing
10'	1.07×10^3	10'	30'
15'	1.57×10^3	15'	45'
20'	2.07×10^3	20'	60'
25'	2.57×10^3	25'	75'
30'	3.07×10^3	30'	90'
35'	3.57×10^3	35'	105'
40'	4.07×10^3	40'	120'
45'	4.57×10^3	45'	135'
50'	5.07×10^3	50'	150'
55'	5.57×10^3	55'	165'
60'	6.07×10^3	60'	180'
65'	6.57×10^3	65'	195'
70'	7.07×10^3	70'	210'
75'	7.57×10^3	75'	225'
80'	8.07×10^3	80'	240'

K taper lengths have been rounded off.
L=Length of Taper (ft.)
W=Width of Taper (ft.)
S=Rated Speed (mph)

SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS

Sheet No.	Operations Standard	Traffic Standard
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
8	8	8
9	9	9
10	10	10
11	11	11
12	12	12
13	13	13
14	14	14
15	15	15
16	16	16
17	17	17
18	18	18
19	19	19
20	20	20
21	21	21
22	22	22
23	23	23
24	24	24
25	25	25
26	26	26
27	27	27
28	28	28
29	29	29
30	30	30
31	31	31
32	32	32
33	33	33
34	34	34
35	35	35
36	36	36
37	37	37
38	38	38
39	39	39
40	40	40
41	41	41
42	42	42
43	43	43
44	44	44
45	45	45
46	46	46
47	47	47
48	48	48
49	49	49
50	50	50
51	51	51
52	52	52
53	53	53
54	54	54
55	55	55
56	56	56
57	57	57
58	58	58
59	59	59
60	60	60
61	61	61
62	62	62
63	63	63
64	64	64
65	65	65
66	66	66
67	67	67
68	68	68
69	69	69
70	70	70
71	71	71
72	72	72
73	73	73
74	74	74
75	75	75
76	76	76
77	77	77
78	78	78
79	79	79
80	80	80
81	81	81
82	82	82
83	83	83
84	84	84
85	85	85
86	86	86
87	87	87
88	88	88
89	89	89
90	90	90
91	91	91
92	92	92
93	93	93
94	94	94
95	95	95
96	96	96
97	97	97
98	98	98
99	99	99
100	100	100

BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

Sheet No.	Operations Standard	Traffic Standard
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
8	8	8
9	9	9
10	10	10
11	11	11
12	12	12
13	13	13
14	14	14
15	15	15
16	16	16
17	17	17
18	18	18
19	19	19
20	20	20
21	21	21
22	22	22
23	23	23
24	24	24
25	25	25
26	26	26
27	27	27
28	28	28
29	29	29
30	30	30
31	31	31
32	32	32
33	33	33
34	34	34
35	35	35
36	36	36
37	37	37
38	38	38
39	39	39
40	40	40
41	41	41
42	42	42
43	43	43
44	44	44
45	45	45
46	46	46
47	47	47
48	48	48
49	49	49
50	50	50
51	51	51
52	52	52
53	53	53
54	54	54
55	55	55
56	56	56
57	57	57
58	58	58
59	59	59
60	60	60
61	61	61
62	62	62
63	63	63
64	64	64
65	65	65
66	66	66
67	67	67
68	68	68
69	69	69
70	70	70
71	71	71
72	72	72
73	73	73
74	74	74
75	75	75
76	76	76
77	77	77
78	78	78
79	79	79
80	80	80
81	81	81
82	82	82
83	83	83
84	84	84
85	85	85
86	86	86
87	87	87
88	88	88
89	89	89
90	90	90
91	91	91
92	92	92
93	93	93
94	94	94
95	95	95
96	96	96
97	97	97
98	98	98
99	99	99
100	100	100


DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

TYPE 3 BARRICADES


1. Refer to the Commodity Work Zone Traffic Control Devices List (CZTDL) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
2. Type 3 Barricades shall be used in the following situations:
 - a. When used to warn of a hazard or obstruction.
 - b. When used to warn of a hazard or obstruction.
 - c. When used to warn of a hazard or obstruction.
3. Barricades extending across a roadway should have a minimum height of 36 inches and a maximum height of 48 inches. The barricade should be placed in the center of the roadway, with the front of the barricade facing the direction of travel. The barricade should be placed in the center of the roadway, with the front of the barricade facing the direction of travel.
4. Stripping of rolls, for the right side of the roadway, should slope down to the left, for the left side of the roadway, should slope down to the right.
5. Identification markings may be placed on the back of the barricade rolls. The maximum height of letters and company logos used for identification shall be 1".
6. Barricades shall not be placed parallel to traffic unless on adequate supports.
7. Barricades shall not be placed parallel to traffic unless on adequate supports.
8. Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cottonless sand is recommended. The use of sandbags shall be based on the weight of the barricade roll. The weight of sandbags shall be based on the weight of the barricade roll. The weight of sandbags shall be based on the weight of the barricade roll.
9. Barricades shall not be placed parallel to traffic unless on adequate supports.

Barricades shall NOT be used as a sign support.

TYPICAL STRIPING DETAIL FOR BARRICADE RAIL




TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES



TRAFFIC CONTROL FOR MATERIAL STOCKPILES


Each roadway of a divided highway shall be barricaded in the same manner.

PERSPECTIVE VIEW



TYPE 3 BARRICADE (POST AND SKID) TYPICAL APPLICATION

CONES



TWO-PIECE CONES


ONE-PIECE CONES

TUBULAR MARKER

28" Cones shall have a minimum weight of 9 1/2 lbs. 42" 2-piece cones shall have a minimum weight of 30 lbs., including bases.

1. Traffic cones and tubular markers shall be prearranged in groups, and meet the height and weight requirements shown above.
2. One-piece cones have the body and base of the cone joined in one conical shape. Two-piece cones have a separate base and body. The base of the cone shall be placed in the center of the roadway, with the front of the cone facing the direction of travel.
3. Two-piece cones may have a base or top extending up to 8" above the main height shown. In order to aid in reflecting the device, reflective material shall be placed on the base and top of the cone.
4. Cones or tubular markers used or left shall have white or white and orange reflective bands as shown above. The reflective bands shall have a width of 4 inches and be spaced at 12 inches. The reflective bands shall have a width of 4 inches and be spaced at 12 inches.
5. 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined in Section 65-11. These should not be used for long-term stationary work unless personnel is on-site to maintain them in the proper position. In the case of long-term stationary work, the reflective bands shall have a width of 4 inches and be spaced at 12 inches.
6. 42" two-piece cones, vertical panels or drums are suitable for all work zone duration.
7. Cones or tubular markers used on each project should be of the same size and shape.

CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS



PERSPECTIVE VIEW


1. Where possible, no/reflectivity is provided, drums are used to warn of a hazard or obstruction.
2. Plastic construction fencing may be used with drums for safety as defined in the plans.
3. Vertical panels on flexible supports may be substituted for drums when the shoulder width is less than 4 feet. When the shoulder width is greater than 4 feet, drums are used.
4. Drums are used to warn of a hazard or obstruction.
5. Drums are used to warn of a hazard or obstruction.

LEGEND

1	Plastic drum
2	Plastic drum with steady burn light
3	Plastic drum with steady burn light and yellow warning reflector
4	Steady burn warning light
5	Yellow warning reflector

THIS DEVICE SHALL NOT BE USED ON PROJECTS LATER THAN MARCH 2014.

EDGE LINE CHANNELIZER



1. This device is intended only for use in a lane of a vertical curve to warn of a hazard or obstruction. It is not to be used in a lane of a horizontal curve.
2. This device shall not be used to separate lanes of traffic traveling in opposite directions or to warn of a hazard or obstruction.
3. This device is based on a 42 inch, two-piece cone with an alternate striping pattern. A then reflective bands, which are spaced at 12 inches. The reflective bands shall have a width of 4 inches and be spaced at 12 inches.
4. The base shall have a minimum of 30 lbs.

SHEET 10 OF 12

BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC(10)-14

DATE	BY	CHKD	APP'D	REV	DESCRIPTION
9-07	8-14				
7-13					
10					

DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

GENERAL

1. The contractor shall be responsible for maintaining work zone and existing pavement markings in accordance with the standard specifications and speed provisions and all roadway open to traffic within the 0.01 miles driver observation window in the plans.
2. Color, patterns and dimensions shall be in conformance with the Manual on Uniform Traffic Control Devices (MUTCD).
3. Additional supplemental pavement marking details may be found in the plans or specifications.
4. Pavement markings shall be installed in accordance with the MUTCD and as shown on the plans.
5. When storm drain markings are required on the plans, either term markings shall conform with the MUTCD, the plans and details on shown on the Standard Plan Sheet W215PM.
6. When standard pavement markings are not in place and the roadway is opened to traffic, 0.01 PASS signs shall be erected to mark the beginning of the section where lighting is provided, and PASS with date signs at the beginning of sections where posting is permitted.
7. All work zone pavement markings shall be installed in accordance with Item 602, "Work Zone Pavement Markings."

RAISED PAVEMENT MARKERS

1. Raised pavement markers are to be placed according to the patterns on BC1121.
2. All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Specification DMS-4200 or DMS-4300.

PREFABRICATED PAVEMENT MARKINGS

1. Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
2. Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


MAINTAINING WORK ZONE PAVEMENT MARKINGS

1. The Contractor will be responsible for maintaining work zone placement markings within the work limits.
2. Work zone placement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 559.
3. The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile headlight beams at night, unless sight distance is restricted by roadway geometrics.
4. Markings failing to meet this criteria within the first 30 days after placement will be replaced at the expense of the Contractor as per Specification Item 652.

REMOVAL OF PAVEMENT MARKINGS

1. Payment markings that are no longer valid, could or cause confusion or prevent a marking that is to be placed on the roadway, or prevent a marking that is to be placed on the roadway, shall be removed or obliterated before the roadway is opened to traffic.
2. The above shall not apply to markings in place for less than three months.
3. Payment markings shall be removed to the fullest extent possible and the roadway shall be restored to its original condition.
4. The removal of payment markings may require resurfacing or seal coating portions of the roadway as described in Item 67.
5. Subject to the approval of the Engineer, any method that proves to be effective on a particular type payment may be used.
6. Blasting cannot be used but will not be required unless specifically shown in the plans.
7. Over-painting of the markings shall NOT be permitted.
8. Removal of raised pavement markers shall be as directed by the Engineer.
9. Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677 - "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS" - unless otherwise stated in the plans.
10. Best-practice marking tapes may be used to cover conflicting existing markings for a period less than two weeks when approved by the Engineer.

Temporary Flexible-Reflective Roadway Marker Tabs



STAPLES OR NAILS SHALL NOT BE USED TO SECURE
TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER
TABS TO THE PAVEMENT SURFACE

1. Temporary flexible reflective roadwork signs used as outclosures and advance warning signs shall be placed in accordance with the requirements of 306-62.02.
2. Tests detailed on this sheet are to be imposed and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be included to ensure quality before placement on the roadway.
 - A. Select five (5) or more tests at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
 - B. Select five (5) tests and perform the following tests: Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line, using a medium size passenger vehicle or pickup truck, traveling at a minimum speed of 35 mph, and a maximum speed of 35 to 40 miles per hour. Place 4 (four) tires in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
3. Small design variations may be noted between the manufacturers.
4. Use Standard Signs W21M for tab placement on new pavements. See Standard Sheet 107-1-1 for tab placement on old pavements.

RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

1. Solid pavement markers used as guidances shall be from the requirements of DMS-4200, product 1451, and meet the requirements of DMS-4200.
2. All temporary construction related pavement markers provided on a project shall be of the same manufacturer.
3. Adhesive for guidances shall be bituminous material for application to rubber and for all surfaces, or thermoplastic for concrete surfaces.
4. Guidances shall be designated as:
YELLOW - (two color reflective surface with yellow body).
WHITE - (one color reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS


DEPARTMENTAL MATERIAL SPECIFICATIONS	
PAYMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BOLLARDS	DMS-4300
EPOXY AND ADHESIVES	DMS-5100
BILUMINOUS ADHESIVE FOR PAYMENT MARKERS	DMS-5120
PERMANENT PRE-APPLICATED PAYMENT MARKINGS	DMS-52-40
TEMPORARILY REMOVABLE, PRE-APPLICATED PAYMENT MARKINGS	DMS-52-41
TEMPORARILY FLEXIBLE, REFLECTIVE	DMS-52-42
TEMPORARY MARKING TAPES	DMS-52-42

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tops and other pavement markings can be found at the Material Producer List web address shown on BC(1).

BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS

SHEET 11 OF 12

FILE#	DO-16-DPT	NAME	TROTT	SSN	K0071	DOB	INDOY	SSN	TROTT
© TROTT FORTWOY 1986 REVISED 2-98 9-01 1-02 7-13 11-02 8-14									
DATE	10-2-	TIME	1200T	SSN	K0071	DOB	INDOY	SSN	TROTT
UNIT	0012	PLA	24	ALOS			MIRWAY		
DIRS		COMBAT					C5		
HSD		FORT BRIDG					SHEET NO.		29



LEGEND	
	Type 3 Barricade
	Heavy Work Vehicle
	Trailer Mounted Flipping Arrow Board
	Sign
	Flag
	Orange Warning Device
	Attenuator (TMA)
	Portable Dumpable Material (Siz. 100)
	Traffic Flow
	Flag

[illegible]

```

* conventional Roads only
** Taper lengths have been

```

L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYNOCAL 11510C

GENERAL NOTES

2. All traffic control devices installed, except those exempt with a traffic sign, may be defined as shown, unless otherwise in the plan, or for routine maintenance work, when approved by the Engineer.
3. Roundabouts shall be installed after the DMS-40 ONE LANE.
4. Roundabout sign, but proper sign posting shall be maintained.
5. Sign spacing may be increased or an additional R1-2-7YIELD sign may be used if a concrete warning channel of the flange or R1-2-7YIELD sign is posted 200 to 300 feet before the roundabout.
6. A Shoulder Vehicle with a TMA should be used anytime it can be posted 200 to 100 feet before the roundabout.
7. In advance of the onset of crew exposure without adversely affecting the performance of the work, the TMA should be used to provide advance warning of the work.
8. Traffic control to maintain in place, Type 2 Bar/Ends or other channelizing device may be substituted for the Shoulder Vehicle and TMA.
6. Additional Shoulder Vehicles with TMA may be substituted for the paved work area, next to those shown in order to protect wider work spaces.

TCP (1-2a)

7. RI-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distances. For projects in urban areas, work spaces should be no longer than one half city block. In rural areas on roadways with less than 2000 ADT, work spaces should be no longer than 400 feet.
8. RI-2 "YIELD" sign with RI-2aP "NO OVERTAKING TRAFFIC" plaque shall be placed on a support of a T post minimum mounting height.

TCP (1-2b)







9. Flags are used as two-way radars or other methods of communication to control traffic.
10. Length of work spaces should be based on the ability of flaggers to communicate.
11. If the work space is located near a horizontal or vertical curve, the buffer distances and the status of stopped vehicles (see item 10) should be stopping short distances to the flaggers.
12. Channelizing equipment on the center-line may be omitted when a pilot car is leading traffic and approved by the engineer.
13. Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.

For construction or maintenance contract work, specific project requirements for on-hold vehicles can be found in the project GENERAL NOTES for Item 502, Berricoes, Signs and Traffic Handling.

TRAFFIC CONTROL PLAN
ONE-LANE TWO-WAY
TRAFFIC CONTROL

TCP(1-2)-12

② TWOOT December 1985					
REVISING					
4-90	2-12				
2-94					
1-97					
4-98					
HOU	CON.	SECT	JOS	INT. REPORT	SAT. REPORT
	0012	34	143		65
	DIST	COUNTRY			SHEET NO.
	PART	BEND			51
152					



Texas Department of Transportation
Houston District

**CONSTRUCTION SEQUENCE
FOR MISCELLANEOUS DRIVES**


CSMD TC8010-2009

FILED	DATE	BY	CHKD	DATE	BY	CHKD
1/20/09	1/20/09	1/20/09	1/20/09	1/20/09	1/20/09	1/20/09
REVISED	DATE	BY	CHKD	DATE	BY	CHKD
1/20/09	1/20/09	1/20/09	1/20/09	1/20/09	1/20/09	1/20/09
PROJECT NO.	32	SHEET	32	DATE	1/20/09	BY
COUNTY	0912	SECTION	34	JOB	143	CS
FOR BEID	0912	34	143	CS		

DISCLAIMER:
The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by the publisher for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE:
FILE:

BARRIER DELINEATION WITH MODULAR CLARE SCREENS




NOTES:

1. Length of Safety Glare Fence will be specified elsewhere in the plans.
2. The cumulative nominal length of the modular units shall equal the length of the individual sections of temporary concrete traffic barrier on which they are installed so the joint between barrier sections will not be exposed by any one unit.
3. Panels/locks will be designed such that reflective sheeting conforming with Department Material Specification DMS-8300, Sign Face Material, is applied to the front face of the panels/locks. The sheeting shall be attached to the edge of the panels/locks. The sheeting shall be attached to one panel/lock per section of concrete barrier not to exceed a spacing of 30 feet. Barrier reflectors are not necessary when panels/locks are installed with reflective sheeting as described.
4. Payment for these devices will be under separate Special Specification "Modular Glare Screens for Headlight Barrier."
5. This detail is only intended to show types of locations where Glare Screens would be appropriate. Required signing and other devices shall be as shown elsewhere in the plans.

VERTICAL PANELS & OPPOSING TRAFFIC LANE DIVIDERS (OTLD) SEPARATING TWO-WAY TRAFFIC ON NORMALLY DIVIDED HIGHWAYS

NOTES:

1. When two-lane, two-way traffic control must be maintained on one roadway of a normally divided highway, opposing traffic shall be separated with either temporary traffic barrier, channelizing devices, or a temporary raised separator. The length of the two-way operation. The above typical application is intended to allow the separator device to be used for other types of roads or applications. These locations should be shown elsewhere in the plans.
2. Spacing devices according to the longest spacing shown on the device spacing table in BC(19), but not exceeding 100'.
3. Every fifth device should be on OTLD except when spaced closer to accommodate an intersection. An OTLD should be the fifth device on each side of intersecting streets or roads.
4. Locations where surface turn lanes with opposing or left-turning devices will be required in order to maintain them in their proper position should be noted elsewhere in the plans.



DEPARTMENTAL MATERIAL SPECIFICATIONS

SIGN FACE MATERIALS	DMS-8300
DELINEATORS AND OBJECT MARKERS	DMS-8600
MODULAR CLARE SCREENS FOR HEADLIGHT BARRIER	DMS-9610



Only pre-qualified products shall be used. A copy of the "Compliant Work Zone Traffic Control Devices List" (OTLCD) describes pre-qualified products and their sources and may be found at the following web address:
<http://www.txdot.gov/odot/otherpublications/otlcd.htm>

TRAFFIC CONTROL PLAN TYPICAL DETAILS

WZ(TD) - 13

FILE	WZ(TD) - 13	REV	13001	REV	13001	REV	13001
DATE	REVISION	DATE	REVISION	DATE	REVISION	DATE	REVISION
4-98	1-01	1-01	1-01	1-01	1-01	1-01	1-01
1-01	1-01	1-01	1-01	1-01	1-01	1-01	1-01

Texas Department of Transportation
Operations
Standard



- LEGEND**
- ① 10" CONC PAVEMENT (URCP)
 - ② 6" 11 MONO CURB
 - ③ RIPRAP (LOW STRIP) (4")
 - ④ 4" SIDEWALK (5' WIDE)
 - ⑤ SEEDING AREA
 - ⑥ 2" BLOCK SOD
 - ⑦ MEDIAN NOSE

- NOTES:**
1. ALL DIMENSIONS ARE TO FACE OF CURB UNLESS OTHERWISE NOTED.
 2. FOR ADDITIONAL INFORMATION SEE TYPICAL SECTIONS, SURVEY CONTROL LAYOUTS, ALIGNMENT DATA, DRAINAGE PLAN & PROFILE AND EXISTING UTILITY LAYOUTS.
 3. MINOR ADJUSTMENTS TO HORIZONTAL LOCATION OF UTILITIES IF THE HYDRANT, WATER METERS, ETC., AS APPROVED BY THE ENGINEER.




CIVILCORP, LLC
 FIRM REGISTRATION NUMBER: 10283



CivilCorp
 ENGINEERS - SURVEYORS
 1001 N. W. 10th St., Suite 100
 Fort Worth, TX 76102
 TEL: 817-252-4100 FAX: 817-252-4103

MISSOURI CITY TEXAS
 DEPARTMENT OF PUBLIC WORKS
 SCOTT R. ELMER, P.E., DIRECTOR

TRAMMEL FRESNO ROAD
 ROADWAY
 PLAN & PROFILE
 (STA 36+50 - 42+00)
 SHEET 8 OF 9
 PROJECT NO. 0912 34 143
 COUNTY TARRANT COUNTY
 STATE TEXAS
 DATE 11/11/2016



MATCHLINE STA 31+00

MATCHLINE STA 36+00

SEE DETENTION POND SHEETS FOR MORE INFORMATION



- LEGEND**
- PROPOSED INLET
 - PROPOSED JUNCTION BOX
 - PROPOSED DITCH
 - PROPOSED MANHOLE

NOTES:

1. FOR ADDITIONAL INFORMATION SEE DRAINAGE AREA MAPS AND HYDRAULIC DATA SHEETS.
2. LENGTH OF PIPE SHOWN ON STORM SEWER PLAN AND PROFILE SHEETS ARE FACE LENGTHS FROM INSIDE FACE TO INSIDE FACE OF INLETS AND MANHOLES. SEE HYDRAULIC DATA SHEETS FOR HYDRAULIC LENGTHS.





FIRM REGISTRATION NUMBER: 10283



TRAMMEL FRESNO ROAD			
STORM SEWER			
PLAN & PROFILE			
(STA 31+00 - 36+00)			
STORM SEWER TRUNKLINE "NS"			
SHEET 7 OF 10			
NO. 6	STATE	PROJECT NO.	CS
NO. 6	TEXAS	CONTRACT	NO. 143
NO. 6	FORT BEND	SECTION	NO. 89

...\\D:\CIVIL\CORP\LLC\Active\City of Missouri City\1220160 Trammel-Fresno Road Widening\Drawings\DWG\Drainage\TF*STMP07-NS.dgn



- NOTES:
1. FOR ADDITIONAL INFORMATION SEE DRAINAGE AREA MAPS AND HYDRAULIC DATA SHEETS.
 2. LENGTH OF PIPE SHOWN ON STORM SEWER PLAN AND PROFILE SHEETS ARE FACE LENGTHS FROM INSIDE FACE TO INSIDE FACE OF INLETS AND MANHOLES. SEE HYDRAULIC DATA SHEETS FOR HYDRAULIC LENGTHS.



CIVILCORP, LLC
 FIRM REGISTRATION NUMBER: 10283



11/11/2016





TRAMMEL FRESNO ROAD
STORM SEWER
PLAN & PROFILE
 (STA 36+50 - 42+00)
 STORM SEWER TRUNKLINE "NS"

SHEET 8 OF 10

NO.	STATE	PROJECT NO.	SHEET NO.
1	TEXAS		CS
NO.	COUNTY	CONTRACT NO.	SHEET NO.
1	FORT BEND	0912	34 OF 143

...\\DGN\Drawings\TF-STMP08-NS.dgn





- LEGEND**
- PROPOSED INLET
 - PROPOSED JUNCTION BOX
 - PROPOSED DITCH
 - PROPOSED MANHOLE

- NOTES:**
1. FOR ADDITIONAL INFORMATION SEE DRAINAGE AREA MAPS AND HYDRAULIC DATA SHEETS.
 2. LENGTH OF PIPE SHOWN ON STORM SEWER PLAN AND PROFILE SHEETS ARE FACE LENGTHS FROM INSIDE FACE TO INSIDE FACE OF INLETS AND MANHOLES. SEE HYDRAULIC DATA SHEETS FOR HYDRAULIC LENGTHS.



CIVILCORP, LLC
 FIRM REGISTRATION NUMBER: 10283





CivilCorp
 ENGINEERS - SURVEYORS
 2015 LICENSE NO. 108672
 JASON C. KASPAR
 11/11/2016

MISSOURI CITY TEXAS
 DEPARTMENT OF PUBLIC WORKS
 SCOTT R. ELWELL, P.E., DIRECTOR

TRAMMEL FRESNO ROAD
 STORM SEWER
 PLAN & PROFILE
 (STA 31+00 - 36+50)
 STORM SEWER TRUNKLINE "SS"
 SHEET 7 OF 10

STATE	PROJECT NO.	DATE
TEXAS	0912	3/4
COUNTY	SECT	JOB
FORT BEND	143	99





- NOTES:
- SEE "PROPOSED TYPICAL SECTIONS" FOR PAVEMENT AND SIDEWALK CONSTRUCTION DETAILS.
 - SEE "ROADWAY PLAN & PROFILE" SHEETS FOR PROPOSED PAVEMENT ELEVATIONS.
 - SEE "STORM SEWER PLAN & PROFILE" SHEETS FOR PROPOSED STORM SEWER LINE SIZES, INLET/MANHOLE LOCATIONS, AND ELEVATIONS.
 - PROPOSED STORM SEWER NOT SHOWN IN PROFILE VIEW FOR CLARITY.

- LEGEND
- WATER LINE (CITY)
 - EXISTING STORM SEWER
 - PROPOSED STORM SEWER
 - FIBER OPTIC LINE
 - FORCE MAIN
 - UNDERGROUND ELECTRIC
 - OVERHEAD ELECTRIC
 - UNDERGROUND GAS
 - WATER VALVE
 - FIRE HYDRANT
 - TELEPHONE PULL BOX
 - POWER POLE
 - CUT ANCHOR
 - EXISTING CURB INLET
 - PROPOSED CURB INLET
 - LIGHT POLE
 - EXISTING TRAFFIC FLOW
 - PROPOSED TRAFFIC FLOW

civilcorp
 ENGINEERS - SURVEYORS
 1200 WEST 12TH STREET, SUITE 100
 FORT WORTH, TEXAS 76102
 TEL: 817-332-4100 FAX: 817-332-4101

MISSOURI CITY
 TEXAS
 DEPARTMENT OF PUBLIC WORKS
 SCOTT R. ELMER, P.E. - DIRECTOR

TRAMMEL FRESNO ROAD
 EXISTING UTILITIES
 PLAN & PROFILE
 (STA 31+00 - STA 36+50)
 SHEET 7 OF 10

DATE	STATE	PROJECT NO.	DATE
6	TEXAS	CONTRACT JOB	SHEET NO.
09/12	34	143	134

